# HIGH-PURITY STANDARDS

# Safety Data Sheet acc. to OSHA HCS

Printing date 07/02/2019

Reviewed on 07/02/2019

## **1** Identification

- · Product identifier
- · Trade name: Nickel (µg/mL in 2% HNO3)
- · Article number: 10-36-1

Details of the supplier of the safety data sheet
Manufacturer/Supplier: High-Purity Standards
Address PO Box 41727 Charleston, SC 29423 United States
Telephone +1-843-767-7900
Fax +1-843-767-7906
Website highpuritystandards.com
Email info@highpuritystandards.com

 Information department: Product safety department
 Emergency telephone number: INFOTRAC
 Emergency telephone numbers1-800-535-5053
 Other emergency telephone numbers 1-352-323-3500

# 2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1H290May be corrosive to metals.Skin Corr. 1AH314Causes severe skin burns and eye damage.Eye Dam. 1H318Causes serious eye damage.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: nitric acid
Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.
Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)

US

*Printing date 07/02/2019* 

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 1) If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner. Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification system: · NFPA ratings (scale 0 - 4)
$\begin{array}{c} 0 \\ 3 \\ 0 \\ 0 \end{array} \begin{array}{c} Health = 3 \\ Fire = 0 \\ Reactivity = 0 \end{array}$
HMIS-ratings (scale 0 - 4)
HEALTH3Health = 3FIRE0Fire = 0REACTIVITY0Reactivity = 0
<ul> <li>Other hazards</li> <li>Results of PBT and vPvB assessment</li> <li>PBT: Not applicable.</li> <li>vPvB: Not applicable.</li> </ul>
3 Composition/information on ingredients
• Chemical characterization: Mixtures • Description: Mixture of the substances listed below with nonhazardous additions.
· Dangerous components:
7697-37-2 nitric acid 2.0%
· Chemical identification of the substance/preparation
7440-02-0 nickel 0.001%
7732-18-5 water, distilled, conductivity or of similar purity 97.999%

## **4 First-aid measures**

• Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 07/02/2019

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

IIGH-PURITY

(Contd. of page 2)

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.* 

# 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b> Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
<b>Environmental precautions:</b> No special measures required.	
Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sa	wdust)
Use neutralizing agent.	waasij.
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
<i>PAC-1:</i>	
7697-37-2 nitric acid	0.16 ppm
7440-02-0 nickel	4.5 mg/m <sup>3</sup>
<i>PAC-2:</i>	
7697-37-2 nitric acid	24 ppm
7440-02-0 nickel	50 mg/m <sup>3</sup>
PAC-3:	
7697-37-2 nitric acid	92 ppm
/09/-5/-2 nuric acia	

# 7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

(Contd. on page 4)

US

Printing date 07/02/2019

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 3)

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

#### 7697-37-2 nitric acid

PEL Long-term value: 5 mg/m<sup>3</sup>, 2 ppm

- REL Short-term value: 10 mg/m<sup>3</sup>, 4 ppm Long-term value: 5 mg/m<sup>3</sup>, 2 ppm
- *TLV* Short-term value: 10 mg/m<sup>3</sup>, 4 ppm Long-term value: 5.2 mg/m<sup>3</sup>, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

## • Exposure controls

## · Personal protective equipment:

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

## • Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

HIGH-PURITY STANDARDS

Printing date 07/02/2019

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

**H-PURITY** ANDARDS

(Contd. of page 4)

• Eye protection:

Tightly sealed goggles

General InformationAppearance:Form:LiquidColor:colorlessOdor:CharacteristicOdor threshold:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Melting range:100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Pecomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³ Relative densityNot determined.Not determined.Vapor densityNot determined.Explosion rateNot determined.Explosion in functio:1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1.010 kg/m³ Relative densityNot determined.Not determined.Vapor densityNot determined.Explosition rateNot determined.Explosition rateNot determined.Explosition rateNot determined.	colorless         Characteristic         Not determined.         Inge:       Undetermined.         nge:       100 °C (212 °F)         Not applicable.         nus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.	Appearance: Form: Color: Odor: Odor threshold: pH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	colorless Characteristic Not determined. Not determined. Undetermined. 100 °C (212 °F)	
Form:Liquid color!essOdor:ColorlessOdor:CharacteristicOdor threshold:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Melting range:100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative density Vapor densityNot determined.Vapor densityNot determined.	colorless         Characteristic         Not determined.         Inge:       Undetermined.         nge:       100 °C (212 °F)         Not applicable.         msp:       Not applicable.         nus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1.01014 g/cm³         Not determined.	Form: Color: Odor: Odor threshold: pH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	colorless Characteristic Not determined. Not determined. Undetermined. 100 °C (212 °F)	
Color:colorlessOdor:CharacteristicOdor threshold:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Melting range:100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative density Vapor densityNot determined.Vapor densityNot determined.	colorless         Characteristic         Not determined.         Inge:       Undetermined.         nge:       100 °C (212 °F)         Not applicable.         msp:       Not applicable.         nump:       Not determined.         nump:       Not applicable.         nump:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1.01014 g/cm³         Not determined.         Not determined.<	Color: Odor: Odor threshold: pH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	colorless Characteristic Not determined. Not determined. Undetermined. 100 °C (212 °F)	
Odor:Characteristic Not determined.Odor threshold:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Melting range:Undetermined.Boiling point/Boiling range:100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Upper:23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Relative density1,010 kg/m³ Not determined.Vapor densityNot determined.	Characteristic         Not determined.         Inge:       Undetermined.         nge:       100 °C (212 °F)         Not applicable.         pus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         Not determined.         N	Odor: Odor threshold: pH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	Characteristic Not determined. Not determined. Undetermined. 100 °C (212 °F)	
Odor threshold:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Boiling point/Boiling range:I00 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Relative density Vapor densityNot determined.Vapor density Vapor densityNot determined.	Not determined.         Inge:       Undetermined.         Inge:       100 °C (212 °F)         Not applicable.         Inge:       Not applicable.         Inge:       Not determined.         Inge:       23 hPa (17.3 mm Hg)         Inge:       1.01014 g/cm³ (8.42962 lbs/gal)         Inge:       Not determined.         Not determined.       Not determined.         Not miscible or difficult to mix.       Not determined.	Odor threshold: pH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Not determined. Undetermined. 100 °C (212 °F)	
pH-value:Not determined.pH-value:Not determined.Change in condition Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.Boiling point/Boiling range:Not applicable.Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Yapor densityI,010 kg/m³ Not determined.Vapor density Yapor densityNot determined.Vapor density Yapor densityNot determined.Not determined.Not determined.Yapor density Yapor densityNot determined.Yapor density Yapor densityNot determined.	Not determined.         inge:       Undetermined.         inge:       100 °C (212 °F)         Not applicable.         ings):       Not applicable.         inge:       Not determined.         product is not selfigniting.         Product does not present an explosion hazard.         Not determined.	pH-value: Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Undetermined. 100 °C (212 °F)	
Change in condition Melting point/Melting range:Undetermined. 100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Not determined. Vapor densityNot determined. Not determined.Vapor density Vapor densityNot determined. Not determined.	Inge:       Undetermined.         nge:       100 °C (212 °F)         Not applicable.         pus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.	Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	Undetermined. 100 °C (212 °F)	
Melting point/Melting range:Undetermined.Boiling point/Boiling range:100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Image: Not determined.Lower:Not determined.Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Not determined.Not determined.Vapor densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Not determined.Not determined.	nge:       100 °C (212 °F)         Not applicable.         nus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         Not determined.         Not determined.         Not determined.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.	Melting point/Melting range: Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	100 °C (212 °F)	
Boiling point/Boiling range:100 °C (212 °F)Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Vapor and consistingNot determined.Not determined.	nge:       100 °C (212 °F)         Not applicable.         nus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         Not determined.         Not determined.         Not determined.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.	Boiling point/Boiling range: Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	100 °C (212 °F)	
Flash point:Not applicable.Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Vapor densityNot determined.Kaporation rateNot determined.	Not applicable.         pus):       Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         Not determined.         Not determined.         Not determined.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.	Flash point: Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:		
Flammability (solid, gaseous):Not applicable.Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Kapor and the set of the set	Not applicable.         re:       Not determined.         Product is not selfigniting.         Product does not present an explosion hazard.         Not determined.         Not determined.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.	Flammability (solid, gaseous): Decomposition temperature: Auto igniting: Danger of explosion:	Not applicable	
Decomposition temperature:Not determined.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Kapor atternedNot determined.Not determined.	re: Not determined. Product is not selfigniting. Product does not present an explosion hazard. Not determined. Not determined. 58 °F): 23 hPa (17.3 mm Hg) 1.01014 g/cm <sup>3</sup> (8.42962 lbs/gal) 1,010 kg/m <sup>3</sup> Not determined. Not determined.	Decomposition temperature: Auto igniting: Danger of explosion:	Noi applicable.	
Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Not determined.Lower:Not determined.Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	Product is not selfigniting.         Product does not present an explosion hazard.         Not determined.         S8 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.	Auto igniting: Danger of explosion:	Not applicable.	
Danger of explosion:Product does not present an explosion hazard.Explosion limits: Lower: Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Relative density1,010 kg/m³Relative density Vapor densityNot determined.Vapor density Evaporation rateNot determined.	Product does not present an explosion hazard.         Not determined.         Not determined.         58 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.	Danger of explosion:	Not determined.	
Explosion limits: Lower: Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Relative density1,010 kg/m³ Not determined.Vapor density Evaporation rateNot determined.	Not determined.         Not determined.         58 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.		Product is not selfigniting.	
Lower: Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density: Relative density1,010 kg/m³ Not determined.Vapor density Evaporation rateNot determined.	Not determined.         58 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.	Explosion limits:	Product does not present an explosion hazard.	
Upper:Not determined.Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	Not determined.         58 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.			
Vapor pressure at 20 °C (68 °F):23 hPa (17.3 mm Hg)Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	58 °F):       23 hPa (17.3 mm Hg)         1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.	Lower:	Not determined.	
Density at 20 °C (68 °F):1.01014 g/cm³ (8.42962 lbs/gal)Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	1.01014 g/cm³ (8.42962 lbs/gal)         1,010 kg/m³         Not determined.         Not miscible or difficult to mix.         tanol/water): Not determined.	Upper:	Not determined.	
Bulk density:1,010 kg/m³Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	1,010 kg/m <sup>3</sup> Not determined. Not determined. Not determined. Not miscible or difficult to mix. tanol/water): Not determined.	Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	Not determined. Not determined. Not determined. with Not miscible or difficult to mix. tanol/water): Not determined.	Density at 20 °C (68 °F):	1.01014 g/cm <sup>3</sup> (8.42962 lbs/gal)	
Relative densityNot determined.Vapor densityNot determined.Evaporation rateNot determined.	Not determined. Not determined. with Not miscible or difficult to mix. tanol/water): Not determined.	Bulk density:	$1,010 \text{ kg/m}^3$	
<b>Evaporation rate</b> Not determined.	Not determined. with Not miscible or difficult to mix. tanol/water): Not determined.			
<b>Evaporation rate</b> Not determined.	vith Not miscible or difficult to mix. tanol/water): Not determined.	Vapor density	Not determined.	
Calability in / Minaibility with	Not miscible or difficult to mix. tanol/water): Not determined.	Evaporation rate	Not determined.	
	tanol/water): Not determined.	Solubility in / Miscibility with		
Water: Not miscible or difficult to mix.		Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water): Not determined.	Not determined.	Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:	Not determined.			
Dynamic: Not determined. Kinematic: Not determined.				

Printing date 07/02/2019

Reviewed on 07/02/2019

#### Trade name: Nickel (µg/mL in 2% HNO3)

		(Contd. of page 2
· Solvent content:		
Water:	98.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

## 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

*The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive* 

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7440-02-0 nickel	2B
· NTP (National Toxicology Program)	
7440-02-0 nickel	R
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
	US

(Contd. on page 7)

Printing date 07/02/2019

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 6)

## **12 Ecological information**

IIGH-PURIT

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Generally not hazardous for water
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name	
DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
ADR	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRI ACID)
Transport hazard class(es)	
DOT	
CORROSIVE 8	
Class	8 Corrosive substances



Printing date 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

Reviewed on 07/02/2019

Page 8/10

	(Contd. of pag
Label	8
ADR, IMDG, IATA	
$\wedge$	
8	
Class	8 Corrosive substances
Label	8
Packing group	
DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
Danger code (Kemler):	80
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	Acids
Stowage Category	
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(EQ)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.C
	(AUTDIC (CID) ) 0 UI

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

(NITRIC ACID), 8, III

Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

(Contd. on page 9)

US

Printing date 07/02/2019

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

(	Contd.	of page	8)

• Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7440-02-0 nickel

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

• Chemicals known to cause cancer:

7440-02-0 nickel

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency) (Substances not listed)

7697-37-2 nitric acid

7440-02-0 nickel

7732-18-5 water, distilled, conductivity or of similar purity

• TLV (Threshold Limit Value established by ACGIH)

7440-02-0 nickel

·NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-02-0 nickel

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: nitric acid
Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage.
Precautionary statements Keep only in original container. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 10)

A5

Printing date 07/02/2019

Reviewed on 07/02/2019

Trade name: Nickel (µg/mL in 2% HNO3)

(Contd. of page 9)

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- *Contact: High-Purity Standards*

*Tel:* 843-767-7900 *Fax:* 843-767-7906

· Date of preparation / last revision 07/02/2019 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Ge

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

*vPvB: very Persistent and very Bioaccumulative* 

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Met. Corr.1: Corrosive to metals – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1



