HIGH-PURITY STANDARDS

Safety Data Sheet acc. to OSHA HCS

Printing date 08/23/2019

Reviewed on 08/23/2019

1 Identification	
· Product identifier	
· Trade name: <u>Arsenic 1000 µg/mL in 2% HCL</u>	
· Article number: 10003-2	
 Details of the supplier of the safety data sheet Manufacturer/Supplier: High-Purity Standards PO Box 41727 Charleston, SC 29423 United States Telephone: +1-843-767-7900 Fax: +1-843-767-7906 highpuritystandards.com Email: info@highpuritystandards.com 	
 Information department: Product safety department Emergency telephone number: INFOTRAC Emergency telephone numbers1-800-535-5053 Other emergency telephone numbers 1-352-323-3500 	
2 Hazard(s) identification	
· Classification of the substance or mixture	
GHS08 Health hazard	
Carc. 1A H350 May cause cancer.	
GHS05 Corrosion	
Skin Corr. 1A H314 Causes severe skin burns and eye damage.	

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



- · Signal word Danger
- Hazard-determining components of labeling: hydrochloric acid arsenic
 Hazard statements H314 Causes severe skin burns and eye damage. H350 May cause cancer.
- **Precautionary statements** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.


(Contd. on page 2)

US

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL



· Dangerous	components:	
7647-01-0	hydrochloric acid	2.0%
7440-38-2	arsenic	0.1%
· Chemical i	dentification of the substance/preparation	
7732-18-5	water, distilled, conductivity or of similar purity	97.9%

4 First-aid measures

· Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

(Contd. of page 2)

- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor. • Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Mount respiratory protective device.	
Wear protective equipment. Keep unprotected persons away.	
• Environmental precautions: No special measures required.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdus	st).
Use neutralizing agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
• PAC-1:	
7647-01-0 hydrochloric acid	1.8 ppm
7440-38-2 arsenic	1.5 mg/m ³
· PAC-2:	
7647-01-0 hydrochloric acid	22 ppm
7440-38-2 arsenic	17 mg/m³
· PAC-3:	
7647-01-0 hydrochloric acid	100 ppm
7440-38-2 arsenic	100 mg/m ³

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

US

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

(Contd. of page 3)

Open and handle receptacle with care.

Prevent formation of aerosols.

• Information about protection against explosions and fires: Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:
7647-01-0 hydrochloric acid
PEL Ceiling limit value: 7 mg/m ³ , 5 ppm
REL Ceiling limit value: 7 mg/m ³ , 5 ppm
TLV Ceiling limit value: 2.98 mg/m ³ , 2 ppm
7440-38-2 arsenic
PEL Long-term value: 0.5* 0.01** mg/m ³ as As; *organic**inorg. compds.; 29 CFR 1910.1018
REL Ceiling limit value: 0.002 mg/m ³ as As; 15min; See Pocket Guide App. A
TLV Long-term value: 0.01 mg/m ³ as As; BEI
· Ingredients with biological limit values:
7440-38-2 arsenic
BEI 35 μg As/L Medium: urine Time: end of workweek Parameter: Inorganic arsenic plus methylated metabolites (background)
• Additional information: The lists that were valid during the creation were used as basis.
 Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

US

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

(Contd. of page 4) · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • Eye protection: Tightly sealed goggles

Physical and chemical proper		
Information on basic physical and	chemical properties	
General Information		
Appearance: Form:	Liquid	
Color:	colorless	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

	(Co	ontd. of page
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.00773 g/cm ³ (8.40951 lbs/gal)	
· Bulk density:	1,008 kg/m ³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	97.9 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.1 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

7647-01-0 hydrochloric acid

Oral LD50 900 mg/kg (rabbit)

7440-38-2 arsenic

Oral LD50 763 mg/kg (rat)

Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

• on the eye: Strong caustic effect.

• Sensitization: No sensitizing effects known.

(Contd. on page 7)

US

Printing date 08/23/2019

HIGH-PURIT

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

(Contd. of page 6)

3

1

K

• Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7647-01-0 hydrochloric acid

7440-38-2 arsenic

· NTP (National Toxicology Program)

7440-38-2 arsenic

· OSHA-Ca (Occupational Safety & Health Administration)

7440-38-2 arsenic

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Not hazardous for water.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN3264



Safety Data Sheet acc. to OSHA HCS

Printing date 08/23/2019

H-PURITY ANDARDS

Reviewed on 08/23/2019

	((ontd. of pag
IN money shinning name		ontai or pug
UN proper shipping name DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric	acid)
ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGAN	
	(HYDROCHLORIC ACID)	10, 110
IMDG, IATA	CORROSIVE LIQUÍD, ACIDIC, INORGANI	C, N.O.
	(HYDROCHLORIC ACID)	
Transport hazard class(es)		
DOT		
CORROSIVE		
Class	8 Corrosive substances	
Label	8	
Class Label	8 Corrosive substances 8	
Packing group DOT, ADR, IMDG, IATA	Ш	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Corrosive substances	
Danger code (Kemler):	80	
EMS Number:	F-A,S-B	
Segregation groups	Acids	
Stowage Category Stowage Code	B SW2 Clear of living quarters.	
_		
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	<i>l of</i> Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 1 L	
	On cargo aircraft only: 30 L	
ADR		
Excepted quantities (EQ)	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	

Printing date 08/23/2019

HIGH-PURITY

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

	(Contd. of page 8)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (HYDROCHLORIC ACID), 8, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

7647-01-0 hydrochloric acid

• Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

7440-38-2 arsenic

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

7647-01-0 hydrochloric acid

· Proposition 65

• Chemicals known to cause cancer:

7440-38-2 arsenic

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7440-38-2 arsenic

• TLV (Threshold Limit Value established by ACGIH)

7647-01-0 hydrochloric acid

7440-38-2 arsenic

·NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-38-2 arsenic

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 10)

A

A4

A1

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL (Contd. of page 9) · Hazard pictograms GHS05 GHS08 · Signal word Danger · Hazard-determining components of labeling: hydrochloric acid arsenic · Hazard statements H314 Causes severe skin burns and eye damage. H350 May cause cancer. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dusts or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations: · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

• Contact: High-Purity Standards Tel: 843-767-7900 Fax: 843-767-7906 • Date of preparation / last revision 08/23/2019 / -

(Contd. on page 11)

⁻ US

Printing date 08/23/2019

Reviewed on 08/23/2019

Trade name: Arsenic 1000 µg/mL in 2% HCL

GH-PURI

(Contd. of page 10)

• Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Skin Corr. 1A: Skin corrosion/irritation - Category 1A Carc. 1A: Carcinogenicity - Category 1A