1 Identification

- · Product identifier
- · Product Name: Performance Check Solution
- · Part Number: 5081-PC
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

(Contd. on page 2)

Product Name: Performance Check Solution

· HMIS-ratings (scale 0 - 4)

(Contd. of page 1)





- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
1634-04-4	4 Methyl-tert-butyl ether 49.9998			
141-78-6	ethyl acetate	49.9998%		
· Chemical i	· Chemical identification of the substance/preparation			
2921-88-2	chlorpyrifos (ISO)	0.0001%		
319-86-8	delta-BHC	0.0001%		
1861-32-1	chlorthal-dimethyl	0.0001%		
1897-45-6	chlorothalonil (ISO)	0.0001%		

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textbf{Indication of any immediate medical attention and special treatment needed} \ No \ further \ relevant \ information \ available.$

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
1634-04-4	Methyl-tert-butyl ether	50 ppm
141-78-6	ethyl acetate	1,200 ppm

(Contd. on page 3)

Product Name: Performance Check Solution

		(Contd. of page 2)			
2921-88-2	chlorpyrifos (ISO)	0.6 mg/m^3			
1897-45-6	chlorothalonil (ISO)	0.13 mg/m^3			
· PAC-2:	· PAC-2:				
1634-04-4	Methyl-tert-butyl ether	570 ppm			
141-78-6	ethyl acetate	1,700 ppm			
2921-88-2	chlorpyrifos (ISO)	15 mg/m³			
1897-45-6	chlorothalonil (ISO)	1.4 mg/m^3			
· PAC-3:					
1634-04-4	Methyl-tert-butyl ether	5300* ppm			
141-78-6	ethyl acetate	10000** ppm			
2921-88-2	chlorpyrifos (ISO)	44 mg/m³			
1897-45-6	chlorothalonil (ISO)	8.6 mg/m³			

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

	7 .7 .		•. •		7 7
· Components with limit	values that	rommro	monitoring	at the	workniace.
Components with time	rutues titut	require	monuornis	ui iii	workpluce.

1634-04-4 Methyl-tert-butyl ether

TLV Long-term value: 180 mg/m³, 50 ppm

141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m³, 400 ppm REL Long-term value: 1400 mg/m³, 400 ppm

TLV Long-term value: 1440 mg/m³, 400 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Product Name: Performance Check Solution

(Contd. of page 3)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and c General Information	nemem properties
Appearance:	
Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C (131 °F)
Flash point:	< 0 °C (<32 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	460 °C (860 °F)
Decomposition temperature:	Not applicable.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.6 Vol %
Upper:	11.5 Vol %
Vapor pressure at 20 °C (68 °F):	268 hPa (201 mm Hg)
Density at 20 °C (68 °F)	0.82025 g/cm³ (6.84499 lbs/gal)
Relative density	Not applicable.
Vapor density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	er): Not applicable.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.

10 Stability and reactivity

Organic solvents:

VOC content:

Solids content:

· Other information

· Reactivity No further relevant information available.

100.0 %

100.00 % 0.0 %

No further relevant information available.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/14/2019 Reviewed on 03/14/2019

Product Name: Performance Check Solution

(Contd. of page 4)

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot \textbf{\textit{Conditions to avoid}} \ \textit{No further relevant information available}.$
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
1634-04-4	1634-04-4 Methyl-tert-butyl ether		
Oral	LD50	4,000 mg/kg (rat)	
Dermal	LD50	1,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	142 mg/l (rat)	
2921-88-2	2921-88-2 chlorpyrifos (ISO)		
Oral	LD50	135 mg/kg (rat)	
Dermal	LD50	202 mg/kg (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

3	
2 <i>B</i>	
R	
· OSHA-Ca (Occupational Safety & Health Administration)	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- $\cdot \textbf{Recommendation:} \ \textit{Must not be disposed of together with household garbage.} \ \textit{Do not allow product to reach sewage system.}$
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

Product Name: Performance Check Solution

(Contd. of page 5)

UN-Number DOT, ADR, IMDG, IATA	UN1993
UN proper shipping name DOT ADR	Flammable liquids, n.o.s. (Methyl tert-butyl ether, Ethyl acetate) 1993 FLAMMABLE LIQUID, N.O.S. (METHYL tert-BUTYL ETHER, ETHY ACETATE)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (METHYL tert-BUTYL ETHER, ETHY ACETATE)
Transport hazard class(es)	
DOT, ADR, IMDG, IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E, <u>S-E</u> B
Transport in bulk according to Annex II of MARF Code	POL73/78 and the IBC Not applicable.
Transport/Additional information:	
$\stackrel{oldsymbol{ADR}}{Excepted}$ quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL TERT-BUTYL ETHE ETHYL ACETATE), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

I	· Section 313 (Specific toxic chemical listings):				
	Methyl-tert-butyl ether				
1897-45-6	chlorothalonil (ISO)				
,	· TSCA (Toxic Substances Control Act):				
	Methyl-tert-butyl ether				
	ethyl acetate				
319-86-8	delta-BHC				
1897-45-6	chlorothalonil (ISO)				

· Proposition 65

	· Chemicals known to	· Chemicals known to cause cancer:			
319-86-8 delta-BHC		IC Control of the con			
	1897-45-6 chlorotha	alonil (ISO)			

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 7)

Product Name: Performance Check Solution

(Contd. of page 6) · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 2921-88-2 chlorpyrifos (ISO) · Carcinogenic categories · EPA (Environmental Protection Agency) 319-86-8 delta-BHC D· TLV (Threshold Limit Value established by ACGIH) 1634-04-4 Methyl-tert-butyl ether *A3* 2921-88-2 chlorpyrifos (ISO) A4

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





None of the ingredients is listed.

GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 03/14/2019 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3