

## 1 Identification

- **Product identifier**
- **Product Name:** Biodiesel Fuel Standard in Pyridine
- **Part Name:** BD-3515
- **Application of the substance / the mixture** For Laboratory Use Only
- **Uses advised against** Not for Human or Animal Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Spex CertiPrep, LLC.  
203 Norcross Ave, Metuchen,  
NJ 08840 USA  
732-549-7144  
USMet-CRMSales@antylia.com
- **Information department:** product safety department
- **Emergency telephone number:**  
Emergency Phone Number (24 hours)  
CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2      H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2      H351 Suspected of causing cancer.



GHS07

Acute Toxicity - Oral 4      H302 Harmful if swallowed.  
Acute Toxicity - Dermal 4      H312 Harmful in contact with skin.  
Acute Toxicity - Inhalation 4      H332 Harmful if inhaled.  
Skin Irritation 2      H315 Causes skin irritation.  
Eye Irritation 2A      H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
PYRIDINE
- **Hazard statements**  
H225      Highly flammable liquid and vapor.  
H302+H312+H332      Harmful if swallowed, in contact with skin or if inhaled.  
H315      Causes skin irritation.  
H319      Causes serious eye irritation.  
H351      Suspected of causing cancer.
- **Precautionary statements**  
P210      Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233      Keep container tightly closed.  
P240      Ground/bond container and receiving equipment.  
P241      Use explosion-proof electrical/ventilating/lighting/equipment.  
P242      Use only non-sparking tools.

Printing date 01/09/2024

Reviewed on 01/09/2024

Product Name: Biodiesel Fuel Standard in Pyridine

(Contd. of page 1)

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.  
P330 Rinse mouth.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

110-86-1	PYRIDINE	99.2%
----------	----------	-------

· Chemical identification of the substance/preparation

621-71-6	Tricaprin	0.8%
----------	-----------	------

### 4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Immediately call a doctor.

Do not give anything to eat or drink - Do not induce vomiting

· Information for Doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Printing date 01/09/2024

Reviewed on 01/09/2024

Product Name: Biodiesel Fuel Standard in Pyridine

(Contd. of page 2)

- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· <b>PAC-1:</b>		
110-86-1	PYRIDINE	3 ppm
· <b>PAC-2:</b>		
110-86-1	PYRIDINE	19 ppm
· <b>PAC-3:</b>		
110-86-1	PYRIDINE	3600* ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· <b>Components with limit values that require monitoring at the workplace:</b>	
<b>110-86-1 PYRIDINE</b>	
PEL	Long-term value: 15 mg/m <sup>3</sup> , 5 ppm
REL	Long-term value: 15 mg/m <sup>3</sup> , 5 ppm
TLV	Long-term value: 1 ppm
A3	

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

**Product Name: Biodiesel Fuel Standard in Pyridine**

(Contd. of page 3)

**Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

**Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odour Threshold:</b>	Not applicable.

**pH-value:** Not applicable.

**Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	115 °C (239 °F)

**Flash point:** < 23 °C (< 73.4 °F)

**Flammability (solid, gaseous):** Highly flammable.

**Auto igniting:** 482 °C (899.6 °F)

**Decomposition temperature:** Not applicable.

**Ignition temperature:** Product is not selfigniting.

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**Explosion limits:**

<b>Lower:</b>	Not applicable.
<b>Upper:</b>	Not applicable.

**Vapor pressure:** Not determined.

**Density at 20 °C (68 °F)** 0.98185 g/cm<sup>3</sup> (8.19354 lbs/gal)

**Relative density** Not applicable.

**Vapor density** Not applicable.

**Evaporation rate** Not applicable.

**Solubility in / Miscibility with Water:**

Fully miscible.

**Partition coefficient (n-octanol/water):** Not applicable.

**Viscosity:**

<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.

**Solvent content:**

**VOC content:** 0.00 %

**Solids content:** 0.0 %

**Other information** No further relevant information available.

(Contd. on page 5)

Printing date 01/09/2024

Reviewed on 01/09/2024

Product Name: Biodiesel Fuel Standard in Pyridine

(Contd. of page 4)

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

### 110-86-1 PYRIDINE

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	1,121 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

110-86-1 PYRIDINE

2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

(Contd. on page 6)

— US —



Printing date 01/09/2024

Reviewed on 01/09/2024

Product Name: Biodiesel Fuel Standard in Pyridine

(Contd. of page 5)

#### 14 Transport information

· UN-Number	UN1282
· DOT, ADR, IMDG, IATA	
· UN proper shipping name	Pyridine
· DOT	1282 PYRIDINE
· ADR	PYRIDINE
· IMDG, IATA	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	II
· DOT, ADR, IMDG, IATA	
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1282 PYRIDINE, 3, II

#### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	No further relevant information available.
· Sara	
· Section 313 (Specific toxic chemical listings):	
110-86-1	PYRIDINE
· TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
· Hazardous Air Pollutants	
None of the ingredients is listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
110-86-1	PYRIDINE

(Contd. on page 7)

Printing date 01/09/2024

Reviewed on 01/09/2024

Product Name: Biodiesel Fuel Standard in Pyridine

(Contd. of page 6)

· <b>Chemicals known to cause reproductive toxicity for females:</b>
None of the ingredients is listed.
· <b>Chemicals known to cause reproductive toxicity for males:</b>
None of the ingredients is listed.
· <b>Chemicals known to cause developmental toxicity:</b>
None of the ingredients is listed.
· <b>Carcinogenic categories</b>
· <b>EPA (Environmental Protection Agency)</b>
None of the ingredients is listed.
· <b>TLV (Threshold Limit Value)</b>
None of the ingredients is listed.
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>
None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

PYRIDINE

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.

P330 Rinse mouth.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

Spex CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 01/09/2024

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 8)

Printing date 01/09/2024

Reviewed on 01/09/2024

**Product Name: Biodiesel Fuel Standard in Pyridine**

(Contd. of page 7)

LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flammable Liquids 2: Flammable liquids – Category 2  
Acute Toxicity - Oral 4: Acute toxicity – Category 4  
Skin Irritation 2: Skin corrosion/irritation – Category 2  
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
Carcinogenicity 2: Carcinogenicity – Category 2

— US —