

Safety Data Sheet acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

1 Identification

· **Product identifier**

· **Trade name:** C-417

· **Other means of identification**

· **Restrictions**

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

· **Application of the substance / the mixture** For Laboratory Use Only

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

NSI Lab Solutions
7212 ACC Blvd.,
Raleigh, NC 27617
USA

· **Information department:** Product safety department

· **Emergency telephone number:** During normal opening times: +1 (919) 789-3000

* 2 Hazard(s) identification

· **Classification of the substance or mixture**



GHS02 Flame

Flammable liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Reproductive toxicity 2

H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to the nervous system through prolonged or repeated exposure.

Aspiration hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin irritation 2

H315 Causes skin irritation.

Specific target organ toxicity (single exposure) 3

H336 May cause drowsiness or dizziness.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

dichloromethane

n-hexane

parathion (ISO)

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground / bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take action to prevent static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Information pertaining to particular dangers for man and environment:

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	1
FIRE	3
REACTIVITY	0

Health = *1

Fire = 3

Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

* 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

75-09-2	dichloromethane	30–60%
110-54-3	n-hexane	≥20–≤40%
56-38-2	parathion (ISO)	0.1–1%

· Non-hazardous components

52-85-7	famphur	0.1–1%
60-51-5	dimethoate (ISO)	0.1–1%
126-68-1	o,o,o-Triethylphosphorothioate	0.1–1%
297-97-2	O,O-diethyl O-pyrazin-2-yl phosphorothioate	0.1–1%
298-00-0	parathion -methyl (ISO)	0.1–1%
298-02-2	phorate (ISO)	0.1–1%
298-04-4	disulfoton	0.1–1%
3689-24-5	sulfotep (ISO)	0.1–1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

— US —

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
75-09-2	dichloromethane	200 ppm
110-54-3	n-hexane	400 ppm
56-38-2	parathion (ISO)	0.15 mg/m ³
60-51-5	dimethoate (ISO)	2.7 mg/m ³
126-68-1	o,o,o-Triethylphosphorothioate	0.027 ppm
297-97-2	O,O-diethyl O-pyrazin-2-yl phosphorothioate	0.011 mg/m ³
298-00-0	parathion -methyl (ISO)	0.11 mg/m ³
298-02-2	phorate (ISO)	0.0036 mg/m ³
298-04-4	disulfoton	0.20 mg/m ³
3689-24-5	sulfotep (ISO)	0.30 mg/m ³
· PAC-2:		
75-09-2	dichloromethane	560 ppm
110-54-3	n-hexane	2900 ppm
56-38-2	parathion (ISO)	1.5 mg/m ³
60-51-5	dimethoate (ISO)	30 mg/m ³
126-68-1	o,o,o-Triethylphosphorothioate	0.3 ppm
297-97-2	O,O-diethyl O-pyrazin-2-yl phosphorothioate	0.12 mg/m ³
298-00-0	parathion -methyl (ISO)	1.2 mg/m ³
298-02-2	phorate (ISO)	0.040 mg/m ³
298-04-4	disulfoton	0.43 mg/m ³
3689-24-5	sulfotep (ISO)	3.5 mg/m ³
· PAC-3:		
75-09-2	dichloromethane	6900 ppm
110-54-3	n-hexane	8600 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 4)

56-38-2	parathion (ISO)	2.0 mg/m ³
60-51-5	dimethoate (ISO)	170 mg/m ³
126-68-1	o,o,o-Triethylphosphorothioate	1.8 ppm
297-97-2	O,O-diethyl O-pyrazin-2-yl phosphorothioate	0.69 mg/m ³
298-00-0	parathion -methyl (ISO)	3.5 mg/m ³
298-02-2	phorate (ISO)	0.12 mg/m ³
298-04-4	disulfoton	2.1 mg/m ³
3689-24-5	sulfotep (ISO)	10 mg/m ³

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

75-09-2 dichloromethane

PEL Short-term value: 125 ppm

Long-term value: 25 ppm

see 29 CFR 1910.1052

REL See Pocket Guide App. A

TLV Long-term value: 174 mg/m³, 50 ppm

BEI, A3

110-54-3 n-hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 5)

REL	Long-term value: 180 mg/m ³ , 50 ppm
TLV	Long-term value: 176 mg/m ³ , 50 ppm
	Skin; BEI

· **Ingredients with biological limit values:**

75-09-2 dichloromethane

BEI	0.3 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Dichloromethane (semi-quantitative)

110-54-3 n-hexane

BEI	0.5 mg/L
	Medium: urine
	Time: end of shift
	Parameter: 2,5-Hexanedione without hydrolysis

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 7)

— US —

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 6)

· **Body protection:** Protective work clothing

* 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Physical state	Liquid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	40 °C (104 °F)
· Flammability:	Highly flammable.
· Explosion limits:	
· Lower:	1.2 Vol %
· Upper:	22 Vol %
· Flash point:	-26 °C (-14.8 °F)
· Auto igniting:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Dynamic:	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure at 20 °C (68 °F):	453 hPa (339.8 mm Hg)
· Vapor pressure:	
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Particle characteristics	Not applicable.

· Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Solvent content:	
· Organic solvents:	98.8 %
· VOC content:	39.88 %
	398.8 g/l / 3.33 lb/gal
· Solids content:	0.6 %
· Change in condition	
· Evaporation rate	Not determined.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 7)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	2,716 mg/kg (rat)
------	------	-------------------

75-09-2 dichloromethane

Oral	LD50	1,600 mg/kg (rat)
------	------	-------------------

Inhalative	LC50/4 h	88 mg/l (rat)
------------	----------	---------------

56-38-2 parathion (ISO)

Oral	LD50	2 mg/kg (rat)
------	------	---------------

Dermal	LD50	6.8 mg/kg (rat)
--------	------	-----------------

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Interactive effects** No interactive effects between components are known.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

75-09-2 dichloromethane

2A

56-38-2 parathion (ISO)

2B

298-00-0 parathion -methyl (ISO)

3

- **NTP (National Toxicology Program)**

75-09-2 dichloromethane

R

- **OSHA-Ca (Occupational Safety & Health Administration)**

75-09-2 dichloromethane

- **Alternative sources for toxicological information** No non-standard sources for toxicological information where used.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 9)

— US —

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 8)

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT, IMDG, IATA**

UN1993

- **UN proper shipping name**

- **DOT**

Flammable liquids, n.o.s. (Hexanes)

- **IMDG**

FLAMMABLE LIQUID, N.O.S. (HEXANES, phorate (ISO)), MARINE POLLUTANT

- **IATA**

Flammable liquid, n.o.s. (HEXANES)

- **Transport hazard class(es)**

- **DOT**



- **Class**

3 Flammable liquids

- **Label**

3

- **IMDG**



- **Class**

3 Flammable liquids

- **Label**

3

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 9)

· IATA 	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: n-hexane
· Marine pollutant:	Symbol (fish and tree)
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	B
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEXANES), 3, II, ENVIRONMENTALLY HAZARDOUS

*15 Regulatory information

After February 3, 2025, this chemical substance (as defined in TSCA section 3(2))/product cannot be distributed in commerce to retailers. After January 28, 2026, this chemical substance (as defined in TSCA section 3(2))/product is and can only be distributed in commerce or processed with a concentration of methylene chloride equal to or greater than 0.1% by weight for the following purposes: (1) Processing as a reactant; (2) Processing for incorporation into a formulation, mixture, or reaction product; (3) Processing for repackaging; (4) Processing for recycling; (5) Industrial or commercial use as a laboratory chemical; (6) Industrial or commercial use as a bonding agent for solvent welding; (7) Industrial and commercial use as a paint and coating remover from safety critical, corrosion-sensitive components of aircraft and spacecraft; (8) Industrial and commercial use as a processing aid; (9) Industrial and commercial use for plastic and rubber products manufacturing; (10) Industrial and commercial use as a solvent that becomes part of a formulation or mixture, where that formulation or mixture will be used inside a manufacturing process, and the solvent (methylene chloride) will be reclaimed; (11) Industrial and commercial use in the refinishing for wooden furniture, decorative pieces, and architectural fixtures of artistic, cultural or historic value until May 8, 2029; (12) Industrial and commercial use in adhesives and sealants in aircraft, space vehicle, and turbine applications for structural and safety critical non-structural applications until May 8, 2029; (13) Disposal; and (14) Export.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 10)

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

56-38-2	parathion (ISO)
60-51-5	dimethoate (ISO)
297-97-2	O,O-diethyl O-pyrazin-2-yl phosphorothioate
298-00-0	parathion -methyl (ISO)
298-02-2	phorate (ISO)
298-04-4	disulfoton
3689-24-5	sulfotep (ISO)

· Section 313 (Specific toxic chemical listings):

75-09-2	dichloromethane
110-54-3	n-hexane
52-85-7	famphur
56-38-2	parathion (ISO)
60-51-5	dimethoate (ISO)
298-00-0	parathion -methyl (ISO)

· TSCA (Toxic Substances Control Act):

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

75-09-2	dichloromethane	ACTIVE
110-54-3	n-hexane	ACTIVE
52-85-7	famphur	ACTIVE
60-51-5	dimethoate (ISO)	ACTIVE
297-97-2	O,O-diethyl O-pyrazin-2-yl phosphorothioate	ACTIVE

· Hazardous Air Pollutants

75-09-2	dichloromethane
110-54-3	n-hexane
56-38-2	parathion (ISO)

· Proposition 65
· Chemicals known to cause cancer:

75-09-2	dichloromethane
56-38-2	parathion (ISO)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

110-54-3	n-hexane
----------	----------

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

75-09-2	dichloromethane	L
110-54-3	n-hexane	II

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 11)

56-38-2	parathion (ISO)	C
· TLV (Threshold Limit Value)		
75-09-2	dichloromethane	A3
56-38-2	parathion (ISO)	A4
298-00-0	parathion -methyl (ISO)	A4
298-02-2	phorate (ISO)	A4
298-04-4	disulfoton	A4
3689-24-5	sulfotep (ISO)	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
75-09-2	dichloromethane	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

dichloromethane

n-hexane

parathion (ISO)

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to the nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground / bond container and receiving equipment.

Use explosion-proof [electrical/ventilating/lighting] equipment.

Use non-sparking tools.

Take action to prevent static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

If inhaled: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: C-417

(Contd. of page 12)

Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** - Department Technical Manager
- **Date of previous version** 02/26/2024
- **Date of preparation** 06/30/2026
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flammable liquids 2: Flammable liquids – Category 2
 - Skin irritation 2: Skin corrosion/irritation – Category 2
 - Carcinogenicity 2: Carcinogenicity – Category 2
 - Reproductive toxicity 2: Reproductive toxicity – Category 2
 - Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
 - Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2
 - Aspiration hazard 1: Aspiration hazard – Category 1
- *** Data compared to the previous version altered.**

— US —