Printing date 02/12/2024 Reviewed on 02/12/2024

1 Identification

- · Product identifier
- · Product Name: Instrument Calibration Standard 2
- · Part Name: CL-CAL-2
- · Application of the substance / the mixture For Laboratory Use Only
- · Uses advised against Not for Human or Animal Use
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Spex CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

732-549-7144

USMet-CRMSales@antylia.com

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

hydrofluoric acid

· Hazard statements

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

	s components:	
	nitric acid	5.0%
	hydrofluoric acid	0.3%
	identification of the substance/preparation	
	water, distilled, conductivity or of similar purity	94.24%
87-69-4	(+)-tartaric acid	0.2%
7429-90-5	aluminium	0.01%
7439-89-6	iron	0.01%
7439-92-1		0.01%
	magnesium	0.01%
	manganese	0.01%
	molybdenum	0.01%
7440-02-0		0.01%
7440-09-7	potassium	0.01%
7440-22-4		0.01%
7440-23-5	sodium	0.01%
7440-24-6	strontium	0.01%
7440-28-0		0.01%
7440-31-5	tin	0.01%
7440-32-6		0.01%
7440-36-0		0.01%
7440-38-2		0.01%
7440-39-3	barium	0.01%
	Beryllium from Beryllium Acetate	0.01%
7440-43-9	cadmium	0.01%
7440-47-3	chromium	0.01%
7440-48-4		0.01%
7440-50-8		0.01%
	vanadium	0.01%
7440-66-6		0.01%
7440-70-2	calcium	0.01%
7782-49-2	selenium	0.01%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

7697-37-2 nitric acid	0.16 ppm
7664-39-3 hydrofluoric acid	1.0 ppm
87-69-4 (+)-tartaric acid	1.6 mg/m^3
7439-89-6 iron	3.2 mg/m^3
7439-92-1 lead	0.15 mg/m^3
7439-95-4 magnesium	18 mg/m³
7439-96-5 manganese	$3 mg/m^3$
7439-98-7 molybdenum	30 mg/m^3
7440-02-0 nickel	4.5 mg/m^3
7440-09-7 potassium	2.3 mg/m^3
7440-22-4 silver	0.3 mg/m^3
7440-23-5 sodium	13 mg/m³
7440-24-6 strontium	30 mg/m^3
7440-28-0 thallium	0.06 mg/m^3
7440-31-5 tin	6 mg/m ³
7440-32-6 titanium	30 mg/m ³
7440-36-0 antimony	1.5 mg/m^3
7440-38-2 arsenic	1.5 mg/m^3
7440-39-3 barium	1.5 mg/m^3
7440-41-7 Beryllium from Beryllium Acetate	0.0023 mg/m
7440-43-9 cadmium	0.10 mg/m^3
7440-47-3 chromium	1.5 mg/m^3
7440-48-4 cobalt	0.18 mg/m^3
7440-50-8 copper	$3 mg/m^3$
7440-62-2 vanadium	$3 mg/m^3$
7440-66-6 zinc	6 mg/m^3
7782-49-2 selenium	0.6 mg/m^3

(Contd. on page 4)



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

	(Co	ontd. of page 3)
· PAC-2:		
7697-37-2		24 ppm
	hydrofluoric acid	24 ppm
	(+)-tartaric acid	17 mg/m³
7439-89-6		35 mg/m ³
7439-92-1		120 mg/m³
	magnesium	200 mg/m³
	manganese	5 mg/m ³
	molybdenum	330 mg/m ³
7440-02-0		50 mg/m ³
7440-09-7		25 mg/m ³
7440-22-4		170 mg/m³
7440-23-5		140 mg/m³
7440-24-6		330 mg/m ³
7440-28-0		3.3 mg/m ³
7440-31-5		67 mg/m³
7440-32-6		330 mg/m ³
7440-36-0	· · · · · · · · · · · · · · · · · · ·	13 mg/m³
7440-38-2		17 mg/m³
7440-39-3		180 mg/m³
	Beryllium from Beryllium Acetate	0.025 mg/m ³
7440-43-9		0.76 mg/m ³
7440-47-3		17 mg/m³
7440-48-4		2 mg/m ³
7440-50-8		33 mg/m³
7440-62-2		5.8 mg/m ³
7440-66-6		21 mg/m³
7782-49-2	selenium	6.6 mg/m ³
• PAC-3:		
7697-37-2		92 ppm
	hydrofluoric acid	44 ppm
	(+)-tartaric acid	100 mg/m³
7439-89-6		150 mg/m³
7439-92-1		700 mg/m ³
	magnesium	1,200 mg/m³
	manganese	1,800 mg/m ³
	molybdenum	2,000 mg/m ³
7440-02-0		99 mg/m³
7440-09-7		150 mg/m³
7440-22-4		990 mg/m³
7440-23-5		870 mg/m³
7440-24-6		2,000 mg/m³
7440-28-0		20 mg/m³
7440-31-5		400 mg/m³
7440-32-6		2,000 mg/m³
7440-36-0		80 mg/m³
7440-38-2		100 mg/m³
7440-39-3		1,100 mg/m³
	Beryllium from Beryllium Acetate	0.1 mg/m ³
7440-43-9		4.7 mg/m³
7440-47-3		99 mg/m³
7440-48-4		20 mg/m³
7440-50-8		200 mg/m³
7440-62-2		35 mg/m ³
7440-66-6	zinc	120 mg/m³



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 4)

7782-49-2 selenium

 40 mg/m^3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

7664-39-3 hydrofluoric acid

PEL Long-term value: 1* mg/m³, 3 ppm

as F, *sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m3, 6* ppm

*15-min, as F

TLV Long-term value: 0.5 ppm Ceiling limit value: 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Fluorides (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 5)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



9 Physical and chemical properties

· General Information

· Information on basic physical and chemical properties

· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odour Threshold:	Not applicable.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	83 °C (181.4 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not applicable.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not applicable.
Upper:	Not applicable.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F)	1.02961 g/cm³ (8.5921 lbs/gal)
· Relative density	Not applicable.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Fully miscible.

10 Stability and reactivity

 $\cdot \textit{Reactivity No further relevant information available}.$

· Partition coefficient (n-octanol/water): Not applicable.

· Chemical stability

· Viscosity:

Dynamic: Kinematic:

· Solvent content:

Solids content:

· Other information

Water: VOC content:

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

Not applicable.

Not applicable.

94.2 %

0.00 %

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

7697-37-2 nitric acid

Inhalative LC50/4 h 2.65 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Corrosive

Irritant

· Carcinogenic categories

· Carcinoge	nic cutegories			
· IARC (International Agency for Research on Cancer)				
7439-92-1	lead	2 <i>B</i>		
7440-02-0	nickel	2 <i>B</i>		
7440-38-2	arsenic	1		
7440-41-7	Beryllium from Beryllium Acetate	1		
7440-43-9	cadmium	1		
7440-47-3	chromium	3		
7440-48-4	cobalt	2B		
7782-49-2	selenium	3		
· NTP (Natio	· NTP (National Toxicology Program)			
7439-92-1	lead	R		
7440-02-0	nickel	R		
7440-38-2	arsenic	K		
7440-41-7	Beryllium from Beryllium Acetate	K		
7440-43-9	cadmium	K		
7440-48-4	cobalt	R		
· OSHA-Ca	(Occupational Safety & Health Administration)			
7440-38-2	arsenic			
7440-43-9	cadmium			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- $\cdot \textit{Persistence and degradability} \ \textit{No further relevant information available}.$
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.



Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 7)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

	14	Transport	tinj	formation
--	----	-----------	------	-----------

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
·ADR	3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)
m (1 1 1 ()	

· Transport hazard class(es)

 $\cdot DOT$



· Class 8 Corrosive substances \cdot Label

· ADR, IMDG, IATA



· Class 8 Corrosive substances · Label · Packing group · DOT, ADR, ÎMDG, IATA III· Environmental hazards: Not applicable. · Special precautions for user Warning: Corrosive substances · Hazard identification number (Kemler code): F-A,S-B· EMS Number: · Segregation groups (SGG1) Acids · Stowage Category · Stowage Code SW2 Clear of living quarters. · Segregation Code SG36 Stow "separated from" SGG18-alkalis. SG49 Stow "separated from" SGG6-cyanides · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot ADR$ Code: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG 5L· Limited quantities (LQ)

Code: E1 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), · UN "Model Regulation":

8, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 31	3 (Specific toxic chemical listings):
7697-37-2	nitric acid
7664-39-3	hydrofluoric acid

Printing date 02/12/2024 Reviewed on 02/12/2024

Product Name: Instrument Calibration Standard 2

	(Contd. of page 8)		
	aluminium		
7439-92-1			
	manganese		
7440-02-0			
7440-22-4			
7440-28-0			
7440-36-0			
7440-38-2			
7440-39-3			
	Beryllium from Beryllium Acetate		
7440-43-9			
7440-47-3			
7440-48-4			
7440-50-8			
7440-62-2			
7440-66-6			
7782-49-2	selenium		
· TSCA (Tox	cic Substances Control Act):		
All compor	ents have the value ACTIVE.		
· Hazardous	Air Pollutants		
7664-39-3	hydrofluoric acid		
7439-92-1	lead		
	manganese		
7440-48-4	cobalt		
· Proposition	1 65		
	known to cause cancer:		
7439-92-1			
7440-02-0			
7440-38-2			
	Beryllium from Beryllium Acetate		
7440-43-9			
7440-48-4	cobalt		
	known to cause reproductive toxicity for females:		
None of the	ingredients is listed.		
· Chemicals known to cause reproductive toxicity for males:			
7440-43-9	cadmium		

· Chemicals known to cause developmental toxicity:

7440-43-9 cadmium

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
7439-92-1 lead	B2	
7439-96-5 manganese	D	
7440-22-4 silver	D	
7440-38-2 arsenic	A	
7440-39-3 barium	D, CBD(inh), NL(oral)	
7440-41-7 Beryllium from Beryllium Acetate	B1, K/L(inh), CBD(oral)	
7440-43-9 cadmium	B1	
7440-50-8 copper	D	
7440-66-6 zinc	D, I, II	
7782-49-2 selenium	D	
· TLV (Threshold Limit Value)		
7429-90-5 aluminium	$A\Delta$	

7429-90-5	aluminium	A4
7439-92-1	lead	<i>A3</i>
7439-98-7	molybdenum	A3
7440-02-0	nickel	A5
7440-38-2	arsenic	<i>A1</i>

(Contd. on page 10)

Reviewed on 02/12/2024 Printing date 02/12/2024

Product Name: Instrument Calibration Standard 2

(Contd. of page 9) 7440-39-3 barium A47440-43-9 cadmium A27440-48-4 cobalt *A3* NIOSH-Ca (National Institute for Occupational Safety and Health) 7440-02-0 nickel 7440-38-2 arsenic 7440-43-9 cadmium

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).





- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

hydrofluoric acid

· Hazard statements

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

Spex CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 02/12/2024
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute Toxicity - Dermal 4: Acute toxicity - Category 4
Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Eye Damage 1: Serious eye damage/eye irritation - Category 1