

1 Identification

- **Product identifier**
- **Product Name:** *Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)*
- **Part Name:** *CLPV-DH*
- **Application of the substance / the mixture** *Certified Reference Material*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Spex CertiPrep, LLC.
203 Norcross Ave, Metuchen,
NJ 08840 USA
732-549-7144
USMet-CRMSales@antylia.com*
- **Information department:** *product safety department*
- **Emergency telephone number:**
*Emergency Phone Number (24 hours)
CHEMTREC (800-424-9300)
Outside US: 703-527-3887*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Carcinogenicity 1B

H350 May cause cancer.

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 1

H370 Causes damage to the central nervous system and the visual organs.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to the central nervous system, the kidneys and the cardiovascular system through prolonged or repeated exposure.

- **Label elements**

· **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

- **Hazard pictograms**



GHS02



GHS06



GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

methanol

styrene

carbon disulphide

vinyl acetate

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to the central nervous system and the visual organs.

H373 May cause damage to the central nervous system, the kidneys and the cardiovascular system through prolonged or repeated exposure.

- **Precautionary statements**

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240

Ground/bond container and receiving equipment.

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 1)

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

67-56-1	methanol	98.2%
75-15-0	carbon disulphide	0.2%
100-42-5	styrene	0.2%
108-05-4	vinyl acetate	0.2%
108-10-1	4-methylpentan-2-one	0.2%
591-78-6	hexan-2-one	0.2%

· Chemical identification of the substance/preparation

67-64-1	acetone	0.2%
78-93-3	butanone	0.2%
106-42-3	p-xylene	0.2%
156-59-2	cis-dichloroethylene	0.2%

4 First-aid measures

- Description of first aid measures
- General information:
 - Immediately remove any clothing soiled by the product.
 - Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 - Remove breathing apparatus only after contaminated clothing have been completely removed.
 - In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation:
 - Supply fresh air or oxygen; call for doctor.
 - In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not give anything to eat or drink - Do not induce vomiting
- Information for Doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 2)

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-56-1	methanol	530 ppm
67-64-1	acetone	200 ppm
75-15-0	carbon disulphide	13 ppm
78-93-3	butanone	200 ppm
100-42-5	styrene	20 ppm
108-05-4	vinyl acetate	6.7 ppm
108-10-1	4-methylpentan-2-one	75 ppm
156-59-2	cis-dichloroethylene	140 ppm
591-78-6	hexan-2-one	10 ppm

· **PAC-2:**

67-56-1	methanol	2,100 ppm
67-64-1	acetone	3200* ppm
75-15-0	carbon disulphide	160 ppm
78-93-3	butanone	2700* ppm
100-42-5	styrene	130 ppm
108-05-4	vinyl acetate	36 ppm
108-10-1	4-methylpentan-2-one	500 ppm
156-59-2	cis-dichloroethylene	500 ppm
591-78-6	hexan-2-one	830 ppm

· **PAC-3:**

67-56-1	methanol	7200* ppm
67-64-1	acetone	5700* ppm
75-15-0	carbon disulphide	480 ppm
78-93-3	butanone	4000* ppm
100-42-5	styrene	1100* ppm
108-05-4	vinyl acetate	180 ppm
108-10-1	4-methylpentan-2-one	3000* ppm
156-59-2	cis-dichloroethylene	850 ppm
591-78-6	hexan-2-one	5000* ppm

(Contd. on page 4)

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-56-1 methanol	
PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
75-15-0 carbon disulphide	
PEL	Long-term value: 20 ppm Ceiling limit value: 30; 100* ppm *30-min peak per 8-hr shift
REL	Short-term value: 30 mg/m ³ , 10 ppm Long-term value: 3 mg/m ³ , 1 ppm Skin
TLV	Long-term value: 1 ppm Skin, BEI, A4
100-42-5 styrene	
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m ³ , 100 ppm Long-term value: 215 mg/m ³ , 50 ppm
TLV	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO, A3
108-05-4 vinyl acetate	
REL	Ceiling limit value: 15* mg/m ³ , 4* ppm *15-min
TLV	Short-term value: 15 ppm Long-term value: 10 ppm A3
108-10-1 4-methylpentan-2-one	
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3

(Contd. on page 5)

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 4)

591-78-6 hexan-2-one	
PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 4 mg/m ³ , 1 ppm
TLV	Short-term value: 10 ppm Long-term value: 5 ppm Skin
Ingredients with biological limit values:	
67-56-1 methanol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
75-15-0 carbon disulphide	
BEI	0.5 mg/g creatinine Medium: urine Time: end of shift Parameter: 2-Thioxothiazolidine-4-carboxylic acid (background, nonspecific)
100-42-5 styrene	
BEI	400 mg/g creatinine Medium: urine Time: end of shift Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)
	40 µg/L Medium: urine Time: end of shift Parameter: Styrene
108-10-1 4-methylpentan-2-one	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
591-78-6 hexan-2-one	
BEI	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)

· Flash point: < 23 °C (< 73.4 °F)

· Flammability (solid, gaseous): Highly flammable.

· Ignition temperature: 455 °C (851 °F)

· Decomposition temperature: Not applicable.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	5.5 Vol %
Upper:	44 Vol %

· Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg)

· Density at 20 °C (68 °F) 0.79266-0.79267 g/cm³ (6.61475-6.61483 lbs/gal)

· Relative density Not applicable.

· Vapor density Not applicable.

· Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

Dynamic:	Not applicable.
Kinematic:	Not applicable.

· Solvent content:

Organic solvents:	99.4 %
VOC content:	99.20 %

Solids content: 0.0 %

· Other information No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

- Primary irritant effect:
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Toxic
Product is suspected to cause damage to fertility.
Product is suspected to cause birth defects.

- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

100-42-5	styrene	2A
106-42-3	p-xylene	3
108-05-4	vinyl acetate	2B
108-10-1	4-methylpentan-2-one	2B

· NTP (National Toxicology Program)

100-42-5	styrene	R
----------	---------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.


14 Transport information


· UN-Number	
· DOT, ADR, IMDG, IATA	UN1230
· UN proper shipping name	
· DOT	Methanol
· ADR	1230 METHANOL
· IMDG, IATA	METHANOL


(Contd. on page 8)


Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 7)

· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3, 6.1

· ADR	
	
· Class	3 Flammable liquids
· Label	3+6.1

· IMDG	
	
· Class	3 Flammable liquids
· Label	3/6.1

· IATA	
	
· Class	3 Flammable liquids
· Label	3 (6.1)

· Packing group	
· DOT, ADR, IMDG, IATA	II

· Environmental hazards:	Not applicable.

· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	336
· EMS Number:	F-E,S-D
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	

· Transport/Additional information:	

· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":	UN 1230 METHANOL, 3 (6.1), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara

· **Section 313 (Specific toxic chemical listings):**

67-56-1	methanol
75-15-0	carbon disulphide

(Contd. on page 9)

Printing date 02/28/2023

Reviewed on 02/28/2023

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 8)

100-42-5	styrene
106-42-3	p-xylene
108-05-4	vinyl acetate
108-10-1	4-methylpentan-2-one

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

67-56-1	methanol
75-15-0	carbon disulphide
100-42-5	styrene
106-42-3	p-xylene
108-05-4	vinyl acetate
108-10-1	4-methylpentan-2-one

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-42-5	styrene
108-10-1	4-methylpentan-2-one

· **Chemicals known to cause reproductive toxicity for females:**

75-15-0	carbon disulphide
---------	-------------------

· **Chemicals known to cause reproductive toxicity for males:**

75-15-0	carbon disulphide
591-78-6	hexan-2-one

· **Chemicals known to cause developmental toxicity:**

67-56-1	methanol
75-15-0	carbon disulphide
108-10-1	4-methylpentan-2-one
591-78-6	hexan-2-one

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
78-93-3	butanone	I
106-42-3	p-xylene	I
108-10-1	4-methylpentan-2-one	I
156-59-2	cis-dichloroethylene	II
591-78-6	hexan-2-one	II

· **TLV (Threshold Limit Value)**

67-64-1	acetone	A4
75-15-0	carbon disulphide	A4
100-42-5	styrene	A4
106-42-3	p-xylene	A4
108-05-4	vinyl acetate	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

methanol
styrene
carbon disulphide
vinyl acetate

(Contd. on page 10)

Product Name: Volatiles Mix D, CLP SOW 2/88 & 3/90 (High Level)

(Contd. of page 9)

Hazard statements

- H225 Highly flammable liquid and vapor.
- H331 Toxic if inhaled.
- H350 May cause cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H370 Causes damage to the central nervous system and the visual organs.
- H373 May cause damage to the central nervous system, the kidneys and the cardiovascular system through prolonged or repeated exposure.

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P321 Specific treatment (see on this label).
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: product safety department

Contact:

Spex CertiPrep, LLC.
1-732-549-7144

Date of preparation / last revision 02/28/2023

Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEL: Biological Exposure Limit
- Flammable Liquids 2: Flammable liquids – Category 2
- Acute Toxicity - Inhalation 3: Acute toxicity – Category 3
- Carcinogenicity 1B: Carcinogenicity – Category 1B
- Toxic to Reproduction 2: Reproductive toxicity – Category 2
- Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1
- Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2