

## 1 Identification

### Product identifier

**Product Name:** Gasoline Range Organics (EPA), Alternate Form

**Part Name:** GRO-EPA-2

**Application of the substance / the mixture** For Laboratory Use Only

**Uses advised against** Not for Human or Animal Use

### Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Spex CertiPrep, LLC.  
203 Norcross Ave, Metuchen,  
NJ 08840 USA  
732-549-7144  
USMet-CRMSales@antylia.com

**Information department:** product safety department

#### Emergency telephone number:

Emergency Phone Number (24 hours)  
CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

## 2 Hazard(s) identification

### Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Toxic to Reproduction 2

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure 1

H370 Causes damage to the central nervous system and the visual organs.

### Label elements

**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

### Hazard pictograms



GHS02



GHS06



GHS08

### Signal word

### Hazard-determining components of labeling:

methanol  
toluene

### Hazard statements

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to the central nervous system and the visual organs.

### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Product Name: Gasoline Range Organics (EPA), Alternate Form**

(Contd. of page 1)

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

67-56-1	methanol	99.0%
108-88-3	toluene	0.15%

**Chemical identification of the substance/preparation**

107-83-5	2-methylpentane	0.15%
540-84-1	2,2,4-trimethylpentane	0.15%
95-47-6	o-xylene	0.1%
95-63-6	1,2,4-trimethylbenzene	0.1%
106-42-3	p-xylene	0.1%
108-38-3	m-xylene	0.1%
71-43-2	benzene	0.05%
100-41-4	ethylbenzene	0.05%
142-82-5	heptane	0.05%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Remove breathing apparatus only after contaminated clothing have been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

(Contd. on page 3)

Printing date 11/27/2023

Reviewed on 11/27/2023

Product Name: Gasoline Range Organics (EPA), Alternate Form

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

67-56-1	methanol	530 ppm
107-83-5	2-methylpentane	1,000 ppm
108-88-3	toluene	67 ppm
540-84-1	2,2,4-trimethylpentane	230 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
108-38-3	m-xylene	130 ppm
71-43-2	benzene	52 ppm
100-41-4	ethylbenzene	33 ppm
142-82-5	heptane	500 ppm

### · PAC-2:

67-56-1	methanol	2,100 ppm
107-83-5	2-methylpentane	11000** ppm
108-88-3	toluene	560 ppm
540-84-1	2,2,4-trimethylpentane	830 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
108-38-3	m-xylene	920 ppm
71-43-2	benzene	800 ppm
100-41-4	ethylbenzene	1100* ppm
142-82-5	heptane	830 ppm

### · PAC-3:

67-56-1	methanol	7200* ppm
107-83-5	2-methylpentane	66000*** ppm
108-88-3	toluene	3700* ppm
540-84-1	2,2,4-trimethylpentane	5000* ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-38-3	m-xylene	2500* ppm
71-43-2	benzene	4000* ppm
100-41-4	ethylbenzene	1800* ppm
142-82-5	heptane	5000* ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

(Contd. on page 4)

Product Name: Gasoline Range Organics (EPA), Alternate Form

(Contd. of page 3)

- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters

· Components with limit values that require monitoring at the workplace:

### 67-56-1 methanol

PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm
	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
	Skin
TLV	Short-term value: 250 ppm
	Long-term value: 200 ppm
	Skin; BEI

### 108-88-3 toluene

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm
	BEI, OTO, A4

· Ingredients with biological limit values:

### 67-56-1 methanol

BEI	15 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Methanol (background, nonspecific)

### 108-88-3 toluene

BEI	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)

· Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.
- Respiratory protection:  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Product Name: Gasoline Range Organics (EPA), Alternate Form

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odour Threshold:	Not applicable.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64.7 °C (148.5 °F)

· Flash point: < 23 °C (< 73.4 °F)

· Flammability (solid, gaseous): Highly flammable.

· Auto igniting: 455 °C (851 °F)

· Decomposition temperature: Not applicable.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	5.5 Vol %
Upper:	44 Vol %

· Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg)

· Density: Not applicable.

· Relative density: Not applicable.

· Vapor density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

Dynamic:	Not applicable.
Kinematic:	Not applicable.

· Solvent content:

Organic solvents:	99.9 %
VOC content:	100.00 %

Solids content: 0.0 %

(Contd. on page 6)

Printing date 11/27/2023

Reviewed on 11/27/2023

Product Name: Gasoline Range Organics (EPA), Alternate Form

(Contd. of page 5)

· **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**67-56-1 methanol**

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Toxic  
Product is suspected to cause damage to fertility.  
Product is suspected to cause birth defects.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
95-47-6	o-xylene	3
106-42-3	p-xylene	3
108-38-3	m-xylene	3
71-43-2	benzene	1
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

71-43-2	benzene	K
---------	---------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

71-43-2	benzene	
---------	---------	--

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.









(Contd. on page 7)

Product Name: Gasoline Range Organics (EPA), Alternate Form

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

#### 14 Transport information

· <b>UN-Number</b> · <b>DOT, ADR, IMDG, IATA</b>	UN1230
· <b>UN proper shipping name</b> · <b>DOT</b> · <b>ADR</b> · <b>IMDG, IATA</b>	Methanol 1230 METHANOL METHANOL
· <b>Transport hazard class(es)</b> · <b>DOT</b>	
 	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3, 6.1
· <b>ADR</b>	
 	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3+6.1
· <b>IMDG</b>	
 	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3/6.1
· <b>IATA</b>	
 	
· <b>Class</b> · <b>Label</b>	3 Flammable liquids 3 (6.1)
· <b>Packing group</b> · <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 8)

Printing date 11/27/2023

Reviewed on 11/27/2023

Product Name: Gasoline Range Organics (EPA), Alternate Form

(Contd. of page 7)

· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1230 METHANOL, 3 (6.1), II

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture** No further relevant information available.
- **Sara**

· <b>Section 313 (Specific toxic chemical listings):</b>	
67-56-1	methanol
108-88-3	toluene
95-47-6	o-xylene
95-63-6	1,2,4-trimethylbenzene
106-42-3	p-xylene
108-38-3	m-xylene
71-43-2	benzene
100-41-4	ethylbenzene

· <b>TSCA (Toxic Substances Control Act):</b>	
All components have the value ACTIVE.	

· <b>Hazardous Air Pollutants</b>	
67-56-1	methanol
108-88-3	toluene
540-84-1	2,2,4-trimethylpentane
95-47-6	o-xylene
106-42-3	p-xylene
108-38-3	m-xylene
71-43-2	benzene
100-41-4	ethylbenzene

· <b>Proposition 65</b>	
· <b>Chemicals known to cause cancer:</b>	
71-43-2	benzene
100-41-4	ethylbenzene

· <b>Chemicals known to cause reproductive toxicity for females:</b>	
None of the ingredients is listed.	

· <b>Chemicals known to cause reproductive toxicity for males:</b>	
71-43-2	benzene

· <b>Chemicals known to cause developmental toxicity:</b>	
67-56-1	methanol
108-88-3	toluene
71-43-2	benzene

· Carcinogenic categories		
· EPA (Environmental Protection Agency)		
108-88-3	toluene	II
540-84-1	2,2,4-trimethylpentane	II
95-47-6	o-xylene	I
95-63-6	1,2,4-trimethylbenzene	II
106-42-3	p-xylene	I
108-38-3	m-xylene	I
71-43-2	benzene	A, K/L
100-41-4	ethylbenzene	D
142-82-5	heptane	D

· TLV (Threshold Limit Value)		
108-88-3	toluene	A4

(Contd. on page 9)



Printing date 11/27/2023

Reviewed on 11/27/2023

**Product Name: Gasoline Range Organics (EPA), Alternate Form**

(Contd. of page 8)

95-47-6	<i>o</i> -xylene	A4
106-42-3	<i>p</i> -xylene	A4
108-38-3	<i>m</i> -xylene	A4
71-43-2	benzene	A1
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

71-43-2 benzene

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS06

GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

methanol

toluene

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to the central nervous system and the visual organs.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

Spex CertiPrep, LLC.

1-732-549-7144

· **Date of preparation / last revision** 11/27/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

(Contd. on page 10)

Printing date 11/27/2023

Reviewed on 11/27/2023

---

**Product Name: Gasoline Range Organics (EPA), Alternate Form**

---

(Contd. of page 9)

Acute Toxicity - Inhalation 3: Acute toxicity – Category 3

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1

---

— US —