| 12/04/2014 | Kit Components | |
|--------------|------------------------------|--|
| Product code | Description | |
| MIXSTD-SET | Mix Calibration Standard Set | |
| Components: | | |
| MIXSTD1-100 | Mixed Calibration Standard 1 | |
| MIXSTD2-100 | Mixed Calibration Standard 2 | |
| MIXSTD3-100 | Mixed Calibration Standard 3 | |
| MIXSTD4-100 | Mixed Calibration Standard 4 | |

Mixed Calibration Standard 5

MIXSTD5-100

1 Identification

- · Product identifier
- · Trade name: Mixed Calibration Standard 1
- · Article number: MIXSTD1-100 / 500
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, Inc - 203 Norcross Ave, Metuchen, NJ 08840

- · Information department: product safety department
- · Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Irritant

Irritating to eyes and skin.

- · Information concerning particular hazards for human and environment:
- The product has to be labeled due to the calculation procedure of international guidelines.
- · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wear protective gloves.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

 ${\it If skin irritation occurs: Get medical advice/attention.}$

If eye irritation persists: Get medical advice/attention.

- · Classification system:
- · NFPA ratings (scale 0 4)



Trade name: Mixed Calibration Standard 1

· HMIS-ratings (scale 0 - 4)

(Contd. of page 1)



FIRE 0 F

Fire = 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| | components: | |
|--|---|---------|
| 7697-37-2 | nitric acid | 2.0% |
| · Chemical identification of the substance/preparation | | |
| 7439-92-1 | Lead from Lead Oxide | 0.05% |
| 7782-49-2 | | 0.02% |
| | cadmium (non-pyrophoric) | 0.015% |
| | zinc powder -zinc dust (stabilized) | 0.015% |
| | manganese | 0.01% |
| | Beryllium from Beryllium Acetate | 0.005% |
| 7732-18-5 | water, distilled, conductivity or of similar purity | 97.885% |

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

 $See\ Section\ 7\ for\ information\ on\ safe\ handling.$

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

 $Prevent\ formation\ of\ aerosols.$

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 1

(Contd. of page 2)

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Color: According to product specification

· Odor: Characteristic · Odour Threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 4)

Trade name: Mixed Calibration Standard 1

| | (Contd. of page |
|---|--|
| · Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. 100°C (212°F) |
| · Flash point: | Not applicable. |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Explosion limits: Lower: Upper: | Not determined. Not determined. |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17 mm Hg) |
| · Density at 20 °C (68 °F) · Relative density · Vapour density · Evaporation rate | 1.01875 g/cm³ (8.501 lbs/gal) Not determined. Not determined. Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water | er): Not determined. |
| · Viscosity: Dynamic: Kinematic: | Not determined. Not determined. |
| · Solvent content: Organic solvents: Water: | 0.0 % 97.9 % |
| Solids content: · Other information | 0.1 % No further relevant information available. |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

| ry for Research on Cancer) | |
|----------------------------|---------------------|
| Oxide | 2B |
| | 3 |
| yrophoric) | 1 |
| Beryllium Acetate | 1 |
| • | Oxide yrophoric) |

(Contd. on page 5)

Trade name: Mixed Calibration Standard 1

| | (Contd. of page 4) |
|---|--------------------|
| · NTP (National Toxicology Program) | |
| 7439-92-1 Lead from Lead Oxide | R |
| 7782-49-2 selenium | R |
| 7440-43-9 cadmium (non-pyrophoric) | K |
| 7440-41-7 Beryllium from Beryllium Acetate | K |
| · OSHA-Ca (Occupational Safety & Health Administration) | |
| 7440-43-9 cadmium (non-pyrophoric) | |

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| · UN-Number · DOT, ADR, IMDG, IATA | UN3264 |
|---------------------------------------|--|
| · UN proper shipping name | |
| $\cdot DOT$ | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) |
| | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) |
| $\cdot ADR$ | 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) |
| · IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACI |
| , | SOLUTION) |
| | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) |
| · Transport hazard class(es) | |
| · DOT | |
| | |





· Class· Label8 Corrosive substances8

 $\cdot ADR, IMDG, IATA$



· Class 8 Corrosive substances

· Label

 $(Contd.\ on\ page\ 6)$

Trade name: Mixed Calibration Standard 1

7782-49-2 selenium

7440-43-9 cadmium (non-pyrophoric)

7440-66-6 zinc powder -zinc dust (stabilized)

| | (Contd. of pag | |
|--|---|--|
| Packing group | | |
| DOT, ADR, IMDG, IATA | III | |
| Environmental hazards: | | |
| Marine pollutant: | No | |
| Special precautions for user | Warning: Corrosive substances | |
| Danger code (Kemler): | 80 | |
| EMS Number: | F- A , S - B | |
| Segregation groups | Acids | |
| Transport in bulk according to Annex II of MARPO | DL73/78 and the IBC | |
| Code | Not applicable. | |
| Transport/Additional information: | | |
| ADR | | |
| Excepted quantities (EQ) | Code: E1 | |
| | Maximum net quantity per inner packaging: 30 ml | |
| | Maximum net quantity per outer packaging: 1000 ml | |
| <i>IMDG</i> | | |
| Limited quantities (LQ) | 5L | |
| Excepted quantities (EQ) | Code: E1 | |
| | Maximum net quantity per inner packaging: 30 ml | |
| | Maximum net quantity per outer packaging: 1000 ml | |
| | | |

| 5 Regulatory information | | |
|--|----|--|
| · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara | | |
| · Section 355 (extremely hazardous substances): | | |
| 7697-37-2 nitric acid | | |
| Section 313 (Specific toxic chemical listings): | | |
| 7697-37-2 nitric acid | | |
| 7439-92-1 Lead from Lead Oxide | | |
| 7782-49-2 selenium | | |
| 7440-43-9 cadmium (non-pyrophoric) | | |
| 7440-66-6 zinc powder -zinc dust (stabilized) | | |
| 7439-96-5 manganese | | |
| 7440-41-7 Beryllium from Beryllium Acetate | | |
| · TSCA (Toxic Substances Control Act): | | |
| All ingredients are listed. | | |
| · Proposition 65 | | |
| · Chemicals known to cause cancer: | | |
| 7439-92-1 Lead from Lead Oxide | | |
| 7440-43-9 cadmium (non-pyrophoric) | | |
| 7440-41-7 Beryllium from Beryllium Acetate | | |
| · Chemicals known to cause reproductive toxicity for females: | | |
| None of the ingredients is listed. | | |
| · Chemicals known to cause reproductive toxicity for males: | | |
| 7440-43-9 cadmium (non-pyrophoric) | | |
| · Chemicals known to cause developmental toxicity: | | |
| 7440-43-9 cadmium (non-pyrophoric) | | |
| · Carcinogenic categories | | |
| · EPA (Environmental Protection Agency) | | |
| 7439-92-1 Lead from Lead Oxide | B2 | |

D

B1

D, I, II

Trade name: Mixed Calibration Standard 1

(Contd. of page 6) 7439-96-5 manganese D 7440-41-7 Beryllium from Beryllium Acetate B1, K/L(inh), CBD(oral) · TLV (Threshold Limit Value established by ACGIH) 7439-92-1 Lead from Lead Oxide А3 7440-43-9 cadmium (non-pyrophoric) A2 · NIOSH-Ca (National Institute for Occupational Safety and Health) 7440-43-9 cadmium (non-pyrophoric)

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Causes skin irritation.

Causes serious eve irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wear protective gloves.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

- If eye irritation persists: Get medical advice/attention.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep Inc.

732-549-7144

- $\cdot \textit{Date of preparation / last revision } 12/04/2014 \, / \, -$
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

USA

1 Identification

- · Product identifier
- · Trade name: Mixed Calibration Standard 2
- · Article number: MIXSTD2-100 / 500
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, Inc - 203 Norcross Ave, Metuchen, NJ 08840

- · Information department: product safety department
- · Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Corrosive

Causes burns.

- · Information concerning particular hazards for human and environment:
- The product has to be labeled due to the calculation procedure of international guidelines.
- · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

(Contd. of page 1)

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 2

· HMIS-ratings (scale 0 - 4)

rale 0 - 4)

Health = 3

- HEALTH 3
 FIRE 0 Fin

 REACTIVITY 0 Rea
 - 0 Fire = 0 Reactivity = 0
- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous | components: | | |
|--------------|---|----|-------|
| 7697-37-2 | nitric acid | | 5.0% |
| · Chemical i | dentification of the substance/preparation | | |
| 7439-89-6 | iron | 1 | 1.0% |
| 7440-39-3 | Barium from Barium carbonate | 0. | .01% |
| 7440-48-4 | cobalt | 0. | .01% |
| 7440-50-8 | copper | 0. | .01% |
| | Vanadium from Ammonium trioxovanadate | 0. | .01% |
| 7732-18-5 | water, distilled, conductivity or of similar purity | 93 | 3.96% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Trade name: Mixed Calibration Standard 2

(Contd. of page 2)

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

(Contd. on page 4)

Trade name: Mixed Calibration Standard 2

| | | (Contd. of page 3) |
|---|---|--------------------|
| Color: | According to product specification | |
| · Odor: | Characteristic | |
| · Odour Threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| · Change in condition Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 83 °C (181 °F) | |
| · Flash point: | Not applicable. | |
| · Flammability (solid, gaseous): | Not applicable. | |
| · Ignition temperature: | | |
| Decomposition temperature: | Not determined. | |
| · Auto igniting: | Product is not selfigniting. | |
| · Danger of explosion: | Product does not present an explosion hazard. | |
| · Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17 mm Hg) | |
| · Density at 20 °C (68 °F) | 1.0961 g/cm³ (9.147 lbs/gal) | |
| · Relative density | Not determined. | |
| Vapour density | Not determined. | |
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol/wate | er): Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 0.0 % | |
| Water: | 94.0 % | |
| Solids content: | 1.0 % | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- \cdot on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $\label{thm:condition} \textit{The product shows the following dangers according to internally approved calculation methods for preparations:}$

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 5)

Trade name: Mixed Calibration Standard 2

(Contd. of page 4)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7440-48-4 cobalt 2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| 1 4 70 | | C | . • |
|----------|---------|-------|-----|
| 14 Trans | port in | torma | non |

| · UN-Number | |
|------------------------|--------|
| · DOT, ADR, IMDG, IATA | UN3264 |
| | |

· UN proper shipping name

· DOT

Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution)

Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)

ADR
 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
 IMDG, IATA
 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID

SOLUTION)
CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

- · Transport hazard class(es)
- $\cdot DOT$



· Class· Label8 Corrosive substances8

· ADR, IMDG, IATA



· Class 8 Corrosive substances

(Contd. on page 6)

Trade name: Mixed Calibration Standard 2

None of the ingredients is listed.

| | (Contd. of page |
|--|---|
| Label | 8 |
| Packing group | III |
| DOT, ADR, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Corrosive substances |
| Danger code (Kemler): | 80 |
| EMS Number: | F- A , S - B |
| Segregation groups | Acids |
| Transport in bulk according to Annex II of MARPO | DL73/78 and the IBC |
| Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid), 8, III |

| · Safety, health and environmental regulations/legislation specific for the substance or mixtur | re |
|---|--------------------|
| Sara | |
| Section 355 (extremely hazardous substances): | |
| 7697-37-2 nitric acid | |
| Section 313 (Specific toxic chemical listings): | |
| 7697-37-2 nitric acid | |
| 7440-39-3 Barium from Barium carbonate | |
| 7440-48-4 cobalt | |
| 7440-50-8 copper | |
| 7440-62-2 Vanadium from Ammonium trioxovanadate | |
| TSCA (Toxic Substances Control Act): | |
| All ingredients are listed. | |
| Proposition 65 | |
| Chemicals known to cause cancer: | |
| 7440-48-4 cobalt | |
| Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| Chemicals known to cause developmental toxicity: | |
| None of the ingredients is listed. | |
| Carcinogenic categories | |
| EPA (Environmental Protection Agency) | |
| 7440-39-3 Barium from Barium carbonate | D, CBD(inh), NL(or |
| 7440-50-8 copper | D |
| TLV (Threshold Limit Value established by ACGIH) | · |
| 7440-39-3 Barium from Barium carbonate | |

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Safety Data Sheet acc. to OSHA HCS

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 2

· Hazard pictograms

(Contd. of page 6)



- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep Inc.

732-549-7144

- · Date of preparation / last revision 12/04/2014 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

1 Identification

- · Product identifier
- · Trade name: Mixed Calibration Standard 3
- · Article number: MIXSTD3-100 / 500
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, Inc - 203 Norcross Ave, Metuchen, NJ 08840

- · Information department: product safety department
- · Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Corrosive

Causes burns.



Harmful

Harmful by inhalation, in contact with skin and if swallowed.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wear protective gloves.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

 ${\it If skin irritation occurs: Get medical advice/attention.}$

If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

(Contd. of page 1)

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 3

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions

| Description, Mistaire of the substances tisted below with normal artifacts additions. | |
|---|--------|
| · Dangerous components: | |
| 7697-37-2 nitric acid | 2.0% |
| 7664-39-3 hydrofluoric acid | <0.9% |
| · Chemical identification of the substance/preparation | |
| 7440-38-2 arsenic | 0.05% |
| 7440-21-3 alkali fluorosilicates (NH4) | 0.01% |
| 7439-98-7 molybdenum | 0.01% |
| 7732-18-5 water, distilled, conductivity or of similar purity | 97.03% |
| | |

4 First-aid measures

- · Description of first aid measures
- $\cdot \ General \ information:$

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Trade name: Mixed Calibration Standard 3

(Contd. of page 2)

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

7664-39-3 hydrofluoric acid

PEL Long-term value: 3 ppm

as F

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm

Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine

Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine

Medium: urine

Time: end of shift

Parameter: Fluorides (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

(Contd. of page 3)

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 3

· Protection of hands:



 $The \ glove \ material \ has \ to \ be \ impermeable \ and \ resistant \ to \ the \ product/\ the \ substance/\ the \ preparation.$

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

| Form: Color: According to product specification Color: Characteristic Odour Threshold: Not determined. pH-value: Not determined. Change in condition Melting point/Melting range: Boiling point/Melting range: 100 °C (212 °F) Flash point: Not applicable. Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. - Auto igniting: Product is not selfigniting. - Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1,00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density: Not determined. Vapour density: Not determined. Solubility in / Miscibility with Water: Not officient (n-octanoll/water): Not determined. | 9 Physical and chemical propertie | es · |
|--|--|---|
| General Information Fluid Appearance: Form: Fluid Color: According to product specification Odour Threshold: Not determined. PH-value: Not determined. Change in condition Undetermined. Boiling point/Melting range: 100 °C (212 °F) Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. *Flammability (solid, gaseous): Not applicable. *Poungosition temperature: Not determined. *Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. **Lypor in limits: Not determined. Upper: Not determined. **Vapor pressure at 20 °C (68 °F): 23 APa (17 mm Hg) **Density at 20 °C (68 °F): 23 APa (17 mm Hg) **Papour density Not determined. **Vapour | · Information on basic physical and o | chemical properties |
| Function Fluid Colors According to product specification Colors Characteristic Not determined. | | |
| Color: According to product specification Odour Threshold: Not determined. pH-value: Not determined. Change in condition Melting point/Melting range: 100 °C (212 °F) Flash point: Not applicable. Flamability (solid, gaseous): Not applicable. Flammbility (solid, gaseous): Not applicable. Inition temperature: Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): Not determined. Vapour density: Not determined. | · Appearance: | |
| Odor Characeristic Odor Threshold: Not determined. PH-value: Not determined. Change in condition Meliting point/Melting range: Undetermined. Boiling point/Boiling range: 100 °C (212 °F) Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. Decomposition temperature: Not determined. Danger of explosion: Product is not selfigniting. Danger of explosion imits: Vost determined. Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 30 hPa (17 mm Hg) Evaporation rate Not determined. Vapour density Not determined. Evaporation rate Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: N | | |
| Odour Threshold: Not determined. pH-value: Not determined. Change in condition Melting point/Melting range: 100 °C (212 °F) Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 33 hPa (17 mm Hg) Pensity at 20 °C (68 °F): Not determined. Vapour density Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | | |
| PH-value: Not determined. Change in condition Melting point/Melting range: 100 °C (212 °F) Flash point: Not applicable. Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Not determined. Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.00449 g/cm³ (8.382 lbs/gal) Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kiematic: Not determined. Not determined. Not determined. Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | | |
| Change in condition Melting point/Melting range: Boiling point/Melting range: 100 °C (212 °F) Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Vapour density Not determined. Vapour density Not determined. Vapour density Not determined. Vapour density Not determined. Vapour fonesity Not determined. Vot determined. Vot determined. Not determined. Vot determined. Not determined. Vot determined. Not determined. Not determined. Vot costity: Dynamic: Kinematic: Not determined. Not determined. Solvent content: Organic solvents: Orga | | |
| Melting point/Melting range: Undetermined. Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Kinematic: Not determined. Viscosity: Operation solvents: Organic solvents: 0,0 % Water: 97,0 % | · pH-value: | Not determined. |
| Boiling point/Boiling range: 100 °C (212 °F) Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Pensity at 20 °C (68 °F): Not determined. Vapour density Not determined. Vapour density Not determined. Vapour density Not determined. Vapour density Not determined. Featition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: Q, 0, % Water: O, 97.0 % | · Change in condition | |
| Flash point: Not applicable. Flammability (solid, gaseous): Not applicable. Ignition temperature: Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. *Vapour density Not determined. *Vapour density Not determined. *Vapour density Not determined. *Vapour density Not miscibility with Water: Not miscible or difficult to mix. *Partition coefficient (n-octanol/water): Not determined. *Viscosity: Not determined. *Viscosity: Not determined. *Kinematic: Not determined. *Kinematic: Not determined. *Solvent content: *Organic solvents: 0.0 % *Water: 97.0 % | Melting point/Melting range: | |
| Flammability (solid, gaseous): Not applicable. Ignition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Upper: Not determined. Poensity at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): Not determined. **Relative density Not determined. **Pour density Not determined. **Solubility in / Miscibility with Water: Not miscible or difficult to mix. **Partition coefficient (n-octanol/water): Not determined. **Viscosity: Dynamic: Not determined. **Viscosity: Not | Boiling point/Boiling range: | 100 °C (212 °F) |
| Inition temperature: Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): Not determined. Vapor density Not determined. Vapor density Not determined. Vapor density Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Not determined. Solvent content: Organic solvents: Organic solvents: Organic solvents: Water: 97.0 % | · Flash point: | Not applicable. |
| Decomposition temperature: Not determined. Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 97.0 % | · Flammability (solid, gaseous): | Not applicable. |
| Auto igniting: Product is not selfigniting. Danger of explosion: Product does not present an explosion hazard. Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F) 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | · Ignition temperature: | |
| Danger of explosion: Explosion limits: Lower: Not determined. Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F): Not determined. Not determined. Not determined. Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Kinematic: Not determined. Not determined. Solvent content: Organic solvents: Organic solvents: 97.0 % | Decomposition temperature: | Not determined. |
| Explosion limits: Lower: Upper: Not determined. Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F) 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Kinematic: Not determined. Solvent content: Organic solvents: Organic solvents: 97.0 % | · Auto igniting: | Product is not selfigniting. |
| Lower: Upper: Not determined. Not determined. . Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) . Density at 20 °C (68 °F) 1.00449 g/cm³ (8.382 lbs/gal) . Relative density Not determined. . Vapour density Not determined. . Evaporation rate Not determined. . Solubility in / Miscibility with Water: Not miscible or difficult to mix. . Partition coefficient (n-octanol/water): Not determined. . Viscosity: Dynamic: Kinematic: Not determined. . Not determined. . Solvent content: Organic solvents: Water: 0.0 % 97.0 % | · Danger of explosion: | Product does not present an explosion hazard. |
| Lower: Upper: Not determined. Not determined. . Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) . Density at 20 °C (68 °F) 1.00449 g/cm³ (8.382 lbs/gal) . Relative density Not determined. . Vapour density Not determined. . Evaporation rate Not determined. . Solubility in / Miscibility with Water: Not miscible or difficult to mix. . Partition coefficient (n-octanol/water): Not determined. . Viscosity: Dynamic: Kinematic: Not determined. . Not determined. . Solvent content: Organic solvents: Water: 0.0 % 97.0 % | · Explosion limits: | |
| Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg) Density at 20 °C (68 °F) 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | | Not determined. |
| Density at 20 °C (68 °F) 1.00449 g/cm³ (8.382 lbs/gal) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | Upper: | Not determined. |
| Relative density Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: Organic solvents: 97.0 % | · Vapor pressure at 20 °C (68 °F): | 23 hPa (17 mm Hg) |
| Relative density Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: Organic solvents: 97.0 % | · Density at 20 °C (68 °F) | 1.00449 g/cm³ (8.382 lbs/gal) |
| Evaporation rate Not determined. Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: Organic solvents: 97.0 % | | Not determined. |
| Solubility in / Miscibility with Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | · Vapour density | Not determined. |
| Water: Not miscible or difficult to mix. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | · Evaporation rate | Not determined. |
| Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | · Solubility in / Miscibility with | |
| Viscosity: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 97.0 % | Water: | Not miscible or difficult to mix. |
| Dynamic: Not determined. Kinematic: Not determined. Solvent content: Organic solvents: 0.0 % Water: 97.0 % | · Partition coefficient (n-octanol/water | er): Not determined. |
| Kinematic: Not determined. Solvent content: 0rganic solvents: Organic solvents: 97.0 % | · Viscosity: | |
| Solvent content: Organic solvents: Water: 97.0 % | ~ | |
| Organic solvents: 0.0 % Water: 97.0 % | Kinematic: | Not determined. |
| Water: 97.0 % | | |
| | o a constant of the constant o | |
| Solids content: 0.1 % | Water: | 97.0 % |
| | Solids content: | 0.1 % |

(Contd. on page 5)

Trade name: Mixed Calibration Standard 3

(Contd. of page 4)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7664-39-3 hydrofluoric acid

Oral LD50 1276 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

| · Carcinogenic caie, | egories | |
|----------------------|--|---|
| · IARC (Internation | nal Agency for Research on Cancer) | |
| 7440-38-2 arsenic | ic | 1 |
| · NTP (National To | oxicology Program) | |
| 7440-38-2 arsenic | ic . | K |
| · OSHA-Ca (Occup | pational Safety & Health Administration) | |
| 7440-38-2 arsenic | ic | |

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- $\cdot \textit{Mobility in soil No further relevant information available}.$
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

Trade name: Mixed Calibration Standard 3

(Contd. of page 5)

- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

| Transport information | |
|---|--|
| UN-Number | |
| DOT, ADR, IMDG, IATA | UN3264 |
| UN proper shipping name | |
| DOT | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, hydrofluoric acid) |
| ADR | 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, hydrofluor |
| THE TIME | acid) |
| IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACII hydrofluoric acid) |
| Transport hazard class(es) | |
| DOT | |
| | |
| | |
| | |
| | |
| • | |
| Class | 8 Corrosive substances |
| Label | 8 |
| ADR, IMDG, IATA | |
| , , , , , , , , , , , , , , , , , , , | |
| | |
| | |
| | |
| | |
| Class | 8 Corrosive substances |
| Label | 8 |
| Packing group | |
| DOT, ADR, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Corrosive substances |
| Danger code (Kemler): | 80 |
| EMS Number: | F-A,S-B |
| Segregation groups | Acids |
| Transport in bulk according to Annex II of MARP | OI 73/78 and the IRC |
| Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| - | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| | UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, hydrofluor |
| UN "Model Regulation": | UN3204, Corrosive ilauta, actaic. inorganic. n.o.s. Unitric acta. nvarotiuot |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

(Contd. on page 7)

Trade name: Mixed Calibration Standard 3

(Contd. of page 6) 7664-39-3 hydrofluoric acid · Section 313 (Specific toxic chemical listings): 7697-37-2 nitric acid 7664-39-3 hydrofluoric acid 7440-38-2 arsenic · TSCA (Toxic Substances Control Act): All ingredients are listed. Proposition 65 · Chemicals known to cause cancer: 7440-38-2 arsenic · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Carcinogenic categories · EPA (Environmental Protection Agency) 7440-38-2 arsenic A· TLV (Threshold Limit Value established by ACGIH) 7440-38-2 arsenic *A1* 7439-98-7 molybdenum *A3* · NIOSH-Ca (National Institute for Occupational Safety and Health)

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GIISO7

- · Signal word Warning
- · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Wear protective gloves.

 $We ar\ eye\ protection\ /\ face\ protection.$

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

 ${\it If skin irritation occurs: Get medical advice/attention.}$

If eye irritation persists: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep Inc.

732-549-7144

- · Date of preparation / last revision 12/04/2014 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 3

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

(Contd. of page 7)

USA

1 Identification

- · Product identifier
- · Trade name: Mixed Calibration Standard 4
- · Article number: MIXSTD4-100 / 500
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, Inc - 203 Norcross Ave, Metuchen, NJ 08840

- · Information department: product safety department
- · Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Corrosive

Causes burns.

- · Information concerning particular hazards for human and environment:
- The product has to be labeled due to the calculation procedure of international guidelines.
- · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

(Contd. of page 1)

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 4

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE0Fire = 0REACTIVITY0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous | components: | |
|-------------|---|---------|
| 7697-37-2 | nitric acid | 5.0% |
| | dentification of the substance/preparation | |
| 7440-70-2 | Calcium from Calcium carbonate | 0.1% |
| | Potassium from Potassium nitrate | 0.04% |
| 7440-23-5 | Sodium from Sodium carbonate | 0.02% |
| 7429-90-5 | aluminium | 0.02% |
| 7440-02-0 | nickel | 0.002% |
| | Chromium from Chromium(III) nitrate nonahydrate | 0.002% |
| 7732-18-5 | water, distilled, conductivity or of similar purity | 94.816% |

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Trade name: Mixed Calibration Standard 4

(Contd. of page 2)

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

(Contd. on page 4)

Trade name: Mixed Calibration Standard 4

| | | (Contd. of page 3) |
|---|--|--------------------|
| Color: | According to product specification | |
| · Odor: | Characteristic | |
| · Odour Threshold: | Not determined. | |
| · pH-value: | Not determined. | |
| · Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. 83 °C (181 °F) | |
| · Flash point: | Not applicable. | |
| · Flammability (solid, gaseous): | Not applicable. | |
| · Ignition temperature: | | |
| Decomposition temperature: | Not determined. | |
| · Auto igniting: | Product is not selfigniting. | |
| · Danger of explosion: | Product does not present an explosion hazard. | |
| · Explosion limits: Lower: Upper: | Not determined. Not determined. | |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17 mm Hg) | |
| Density at 20 °C (68 °F) Relative density Vapour density Evaporation rate | 1.02626 g/cm ³ (8.564 lbs/gal) Not determined. Not determined. Not determined. | |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol/wate | r): Not determined. | |
| · Viscosity: Dynamic: Kinematic: | Not determined. Not determined. | |
| · Solvent content: Organic solvents: Water: | 0.0 % 94.8 % | |
| Solids content: Other information | 0.2 % No further relevant information available. | |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 5)

Trade name: Mixed Calibration Standard 4

(Contd. of page 4)

· Carcinogenic categories

| · IARC (International Agency for Research on Cancer) | | |
|--|---|---|
| 7440-02-0 | nickel | 1 |
| 7440-47-3 | Chromium from Chromium(III) nitrate nonahydrate | 3 |

· NTP (National Toxicology Program)

7440-02-0 nickel

R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| 1 4 70 | | | c | . • |
|---------------|---------|------|----------|-----|
| 14 17 | anspor | TIME | mmm | mm |
| 17 1 1 | unsport | رباس | OI III W | wii |

- · UN-Number
- · DOT, ADR, IMDG, IATA

UN3264

- · UN proper shipping name
- $\cdot DOT$
- · ADR · IMDG, IATA

Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

· Label

8

 $\cdot \textit{ADR}, \textit{IMDG}, \textit{IATA}$



· Class 8 Corrosive substances

· Label

(Contd. on page 6)

Trade name: Mixed Calibration Standard 4

| | (Contd. of pag |
|--|---|
| Packing group | |
| DOT, ADR, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Corrosive substances |
| Danger code (Kemler): | 80 |
| EMS Number: | F- A , S - B |
| Segregation groups | Acids |
| Transport in bulk according to Annex II of MARPO | OL73/78 and the IBC |
| Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| · · · · · · · · · · · · · · · · · · · | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| | UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid), 8, III |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

| · Section 35 | 5 (extremely | hazardous | substances): |
|--------------|--------------|-----------|--------------|

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid 7429-90-5 aluminium 7440-02-0 nickel

7440-47-3 Chromium from Chromium(III) nitrate nonahydrate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

7440-02-0 nickel

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

 7429-90-5
 aluminium
 A4

 7440-02-0
 nickel
 A5

· NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-02-0 nickel

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 4

· Hazard pictograms

(Contd. of page 6)



- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep Inc.

732-549-7144

- · Date of preparation / last revision 12/04/2014 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

1 Identification

- · Product identifier
- · Trade name: Mixed Calibration Standard 5
- · Article number: MIXSTD5-100 / 500
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Certified Reference Material
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, Inc - 203 Norcross Ave, Metuchen, NJ 08840

- · Information department: product safety department
- Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Corrosive

Causes burns.



Harmful

Harmful by inhalation, in contact with skin and if swallowed.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 5

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous | components: | |
|--------------|---|---------|
| 7697-37-2 | nitric acid | 5.0% |
| 7664-39-3 | hydrofluoric acid | <0.9% |
| · Chemical i | dentification of the substance/preparation | |
| 87-69-4 | (+)-tartaric acid | <0.9% |
| | magnesium | 0.1% |
| 7440-28-0 | Thallium from Thallium nitrate | 0.02% |
| 7440-36-0 | antimony | 0.02% |
| 7440-42-8 | Boron from Ammonium tetraborate tetrahydrate | 0.01% |
| 7440-22-4 | silver | 0.005% |
| 7732-18-5 | water, distilled, conductivity or of similar purity | 93.045% |

4 First-aid measures

- · Description of first aid measures
- $\cdot \textit{General information:}$

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Trade name: Mixed Calibration Standard 5

(Contd. of page 2)

- $\cdot \textit{Environmental precautions:} \ \textit{Do not allow to enter sewers/surface or ground water.}$
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- $\cdot \textbf{Information about protection against explosions and fires:} \ No \ special \ measures \ required.$
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

- PEL Long-term value: 5 mg/m³, 2 ppm
- REL Short-term value: 10 mg/m³, 4 ppm
 - Long-term value: 5 mg/m³, 2 ppm
- TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

7664-39-3 hydrofluoric acid

PEL Long-term value: 3 ppm

as F

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm

Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine

Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Fluorides (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- $\cdot \textit{Personal protective equipment:}$
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Trade name: Mixed Calibration Standard 5

(Contd. of page 3)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

| 9 Physical and chemical propertie | S |
|---|---|
| · Information on basic physical and c | chemical properties |
| · General Information | |
| · Appearance: | Fluid |
| Form: Color: | According to product specification |
| · Odor: | Characteristic |
| · Odour Threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 83 °C (181 °F) |
| · Flash point: | Not applicable. |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17 mm Hg) |
| · Density | Not determined. |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/wate | er): Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| | (0.11 |

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 5

(Contd. of page 4)

| Water: | 93.0 % | |
|-----------------------------------|---|--|
| Solids content: Other information | 1.1 % No further relevant information available. | |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7664-39-3 hydrofluoric acid

Oral LD50 1276 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- $\cdot Additional\ ecological\ information:$
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

Trade name: Mixed Calibration Standard 5

(Contd. of page 5)

- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

| Transport information | |
|--|--|
| UN-Number | |
| DOT, ADR, IMDG, IATA | UN3264 |
| UN proper shipping name | |
| DOT | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, hydrofluoric acid) |
| ADR | 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, hydrofluor |
| TARGET AND A STATE OF THE STATE | acid) |
| IMDG, IATA | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACII hydrofluoric acid) |
| Transport hazard class(es) | |
| DOT | |
| | |
| | |
| | |
| 8 | |
| • | |
| Class | 8 Corrosive substances |
| Label | 8 |
| ADR, IMDG, IATA | |
| <i>, ,</i> | |
| | |
| | |
| | |
| w . | |
| Class | 8 Corrosive substances |
| Label | 8 |
| Packing group | |
| DOT, ADR, IMDG, IATA | III |
| Environmental hazards: | |
| Marine pollutant: | No |
| * | Waming, Compains substances |
| Special precautions for user Danger code (Kemler): | Warning: Corrosive substances 80 |
| EMS Number: | F-A,S-B |
| Segregation groups | Acids |
| • • • • | |
| Transport in bulk according to Annex II of MARPO Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Excepted quantities (EQ) | Code: E1 |
| - * * | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| | |
| UN "Model Regulation": | UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid, hydrofluor |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

(Contd. on page 7)

Trade name: Mixed Calibration Standard 5

(Contd. of page 6) 7664-39-3 hydrofluoric acid · Section 313 (Specific toxic chemical listings): 7697-37-2 nitric acid 7664-39-3 hydrofluoric acid 7440-28-0 Thallium from Thallium nitrate 7440-36-0 antimony 7440-22-4 silver · TSCA (Toxic Substances Control Act): All ingredients are listed. · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Carcinogenic categories · EPA (Environmental Protection Agency) 7440-42-8 Boron from Ammonium tetraborate tetrahydrate I(oral)7440-22-4 silver D · TLV (Threshold Limit Value established by ACGIH) None of the ingredients is listed. · NIOSH-Ca (National Institute for Occupational Safety and Health)

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms

None of the ingredients is listed.



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

Causes severe skin burns and eye damage.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dusts or mists.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep Inc.

732-549-7144

· Date of preparation / last revision 12/04/2014 / -

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/04/2014 Reviewed on 12/04/2014

Trade name: Mixed Calibration Standard 5

(Contd. of page 7)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LCSO: Lethal concentration, 50 percent

LDSO: Lethal dose, 50 percent

Skin Corr. IB: Skin corrosion/irritation, Hazard Category 18

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1