09/21/2017 Kit Components		
Product code	Description	
MXSTD-SETAN	Set of 5 ICP Calibration Standards w/o Mercury	
Components:		
MIXSTD1A-100	Mixed Calibration Standard 1A	
MIXSTD2A-100	Mixed Calibration Standard 2A	
MIXSTD3A-100	Mixed Calibration Standard 3A	
MXSTD4A-100N	Mixed Calibration Standard 4A	

Mixed Calibration Standard 5A

MIXSTD5A-100

1 Identification

- · Product identifier
- · Product Name: Mixed Calibration Standard 1A
- · Part Number: MIXSTD1A-100
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. Eye Dam. 1

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3Fire = 0

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Product Name: Mixed Calibration Standard 1A

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
7697-37-2 nitric acid		5.0%
Chemical identification of the si	ubstance/preparation	
7664-39-3 hydrofluoric acid		0.1%
87-69-4 (+)-tartaric acid		0.02%
7440-38-2 arsenic		0.01%
7440-70-2 Calcium from Calciu	m carbonate	0.01%
7782-49-2 selenium		0.005%
7440-36-0 antimony		0.005%
7439-96-5 manganese		0.002%
7440-50-8 copper		0.002%
7440-43-9 cadmium (non-pyrop	horic)	0.002%
7440-42-8 Boron from Ammonii	um tetraborate tetrahydrate	0.002%
7440-39-3 Barium from Barium	carbonate	0.001%
7440-22-4 silver		0.001%
7732-18-5 water, distilled, cond	luctivity or of similar purity	94.84%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1.00000000	zenon erner major enemicano	
· PAC-1:		
7697-37-2	nitric acid	0.16 ppm
87-69-4	(+)-tartaric acid	1.6 mg/m3
7440-38-2	arsenic	1.5 mg/m3
7782-49-2	selenium	0.6 mg/m3

(Contd. on page 3)

Product Name: Mixed Calibration Standard 1A

7440-36-0	antimony	(Contd. of page 1.5 mg/m
7439-96-5	manganese	3 mg/m3
7440-50-8	copper	3 mg/m3
7440-43-9	cadmium (non-pyrophoric)	0.10 mg.
7440-42-8	Boron from Ammonium tetraborate tetrahydrate	1.9 mg/1
7440-39-3	Barium from Barium carbonate	1.5 mg/1
7440-22-4	silver	0.3 mg/r
<i>PAC-2:</i>		
7697-37-2	nitric acid	24 ppm
87-69-4	(+)-tartaric acid	17 mg/m
7440-38-2	arsenic	17 mg/n
7782-49-2	selenium	6.6 mg/s
7440-36-0	antimony	13 mg/n
7439-96-5	manganese	5 mg/m3
7440-50-8	copper	33 mg/n
	cadmium (non-pyrophoric)	0.76 mg.
7440-42-8	Boron from Ammonium tetraborate tetrahydrate	21 mg/n
7440-39-3	Barium from Barium carbonate	180 mg/s
7440-22-4	silver	170 mg/s
PAC-3:		
7697-37-2	nitric acid	92 ppm
87-69-4	(+)-tartaric acid	100 mg/n
7440-38-2	arsenic	100 mg/n
7782-49-2	selenium	40 mg/m3
7440-36-0	· · · · · · · · · · · · · · · · · · ·	80 mg/m3
	manganese	1,800 mg.
7440-50-8		200 mg/n
	cadmium (non-pyrophoric)	4.7 mg/m
7440-42-8	Boron from Ammonium tetraborate tetrahydrate	130 mg/n
7440-39-3	Barium from Barium carbonate	1,100 mg.
7440-22-4	silver	990 mg/m

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot \textit{Specific end use}(s) \textit{ No further relevant information available}.$

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm
REL Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5 mg/m³, 2 ppm
TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

(Contd. on page 4)

Product Name: Mixed Calibration Standard 1A

(Contd. of page 3)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

O	Physical	and d		la area i a a l		el an
У.	E NAVNUCCU	unu	KH.	//////////////////////////////////////	MINKINIKAN	<i>I I K</i>

· Information on	hasic	nhyeical	and	chemical	nronerties
· Injormation on	vasic	pnysicai	ana	cnemicai	properties

· General Information

· Appearance:

Liquid Form:

Color: According to product specification

· Odor: Characteristic Not applicable. · Odour Threshold: Not applicable. · pH-value:

· Change in condition

Undetermined Melting point/Melting range: Boiling point/Boiling range: 83 °C (181 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not applicable.

· Danger of explosion: Product does not present an explosion hazard.

Product is not selfigniting.

· Explosion limits:

· Auto igniting:

Not applicable. Lower: Upper: Not applicable.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg)

· Density Not applicable. · Relative density Not applicable. Not applicable. · Vapor density

Not applicable. · Evaporation rate

(Contd. on page 5)

Product Name: Mixed Calibration Standard 1A

		Contd. of page 4)
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not applicable.	
· Viscosity: Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.0~%	
Water:	94.8 %	
Solids content:	0.1 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7440-38-2 arsenic	1
7782-49-2 selenium	3
7440-43-9 cadmium (non-pyrophoric)	1
· NTP (National Toxicology Program)	
7440-38-2 arsenic	K
7440-43-9 cadmium (non-pyrophoric)	K
· OSHA-Ca (Occupational Safety & Health Administration)	
7440-38-2 arsenic	
7440-43-9 cadmium (non-pyrophoric)	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 6)

(Contd. of page 5)

Printing date 09/21/2017 Reviewed on 09/21/2017

Product Name: Mixed Calibration Standard 1A

 $\cdot \textit{Results of PBT and vPvB assessment}$

- · PBT: Not applicable.
- vPvB: Not applicable.
 Other adverse effects No further relevant information available.

13 Disposal considerations

- $\cdot \ Waste \ treatment \ methods$
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution, Hydrofluoric acid)
· ADR · IMDG, IATA	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution, Hydrofluoric acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID
	SOLUTION, HYDROFLUORIC ACID)
· Transport hazard class(es) · DOT	
OORROSIVE	
· Class · Label	8 Corrosive substances 8
· ADR, IMDG, IATA	
· Class · Label	8 Corrosive substances 8
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
 Special precautions for user Danger code (Kemler): EMS Number: Segregation groups Stowage Category Stowage Code 	Warning: Corrosive substances 80 F-A,S-B Acids A SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and Code	l the IBC Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ)	5L

Product Name: Mixed Calibration Standard 1A

(Contd. of page 6) \cdot Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION, HYDROFLUORIC ACID), 8, III · UN "Model Regulation":

	lth and environmental regulations/legislation specific for the substance or mixt	ture
Sara	5 (t	
7697-37-2	5 (extremely hazardous substances):	
	hydrofluoric acid	
Section 31. 7697-37-2	3 (Specific toxic chemical listings):	
	hydrofluoric acid	
7440-38-2		
7782-49-2		
7440-36-0		
	manganese	
7440-50-8		
	cadmium (non-pyrophoric)	
	Barium from Barium carbonate	
7440-22-4		
TSCA (Tox	cic Substances Control Act):	
	nitric acid	
	(+)-tartaric acid	
7440-38-2		
7440-70-2	Calcium from Calcium carbonate	
7782-49-2	· ·	
7440-36-0	antimony	
7439-96-5	manganese	
7440-50-8	copper	
7440-43-9	cadmium (non-pyrophoric)	
7440-42-8	Boron from Ammonium tetraborate tetrahydrate	
7440-39-3	Barium from Barium carbonate	
7440-22-4		
	water, distilled, conductivity or of similar purity	
Proposition		
	known to cause cancer:	
7440-38-2		
	cadmium (non-pyrophoric)	
	known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
Chemicals	known to cause reproductive toxicity for males:	
7440-43-9	cadmium (non-pyrophoric)	
Chemicals	known to cause developmental toxicity:	
7440-43-9	cadmium (non-pyrophoric)	
Carcinoac	nic categories	
-	ronmental Protection Agency)	
7440-38-2		A
7782-49-2		D
	manganese	D
7440-50-8		D D
, 170.20-0	coppe.	

Product Name: Mixed Calibration Standard 1A

(Contd. of page 7) 7440-42-8 Boron from Ammonium tetraborate tetrahydrate I (oral) 7440-39-3 Barium from Barium carbonate D, CBD(inh), NL(oral) 7440-22-4 silver D · TLV (Threshold Limit Value established by ACGIH) 7440-38-2 arsenic A17440-43-9 cadmium (non-pyrophoric) A27440-39-3 Barium from Barium carbonate A4· NIOSH-Ca (National Institute for Occupational Safety and Health) 7440-38-2 arsenic 7440-43-9 cadmium (non-pyrophoric)

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

- · Hazard statements
- H314 Causes severe skin burns and eye damage.
- · Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 09/21/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1

1 Identification

- · Product identifier
- · Product Name: Mixed Calibration Standard 2A
- · Part Number: MIXSTD2A-100
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Lahel elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

Product Name: Mixed Calibration Standard 2A

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	s components:	
7697-37-2	nitric acid	5.0%
	identification of the substance/preparation	
	Potassium from Potassium nitrate	0.02%
7439-98-7	molybdenum	0.01%
7440-23-5	Sodium from Sodium carbonate	0.01%
7439-93-2	Lithium from Lithium carbonate	0.005%
7440-24-6	Strontium from Strontium carbonate	0.001%
7732-18-5	water, distilled, conductivity or of similar purity	94.954%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

 $See \ Section \ 8 \ for \ information \ on \ personal \ protection \ equipment.$

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
7697-37-2 nitric acid	0.16 ppm
	**
7440-09-7 Potassium from Potassium nitrate	2.3 mg/m.
7439-98-7 molybdenum	30 mg/m3
7440-23-5 Sodium from Sodium carbonate	13 mg/m3
7439-93-2 Lithium from Lithium carbonate	3.3 mg/m.
7440-24-6 Strontium from Strontium carbonate	30 mg/m ³
· PAC-2:	
7697-37-2 nitric acid	24 ppm
7440-09-7 Potassium from Potassium nitrate	25 mg/m3
7439-98-7 molybdenum	330 mg/m
7440-23-5 Sodium from Sodium carbonate	140 mg/m
·	(Ct-1

(Contd. on page 3)

Product Name: Mixed Calibration Standard 2A

		(Contd. of page 2)
7439-93-2	Lithium from Lithium carbonate	36 mg/m3
7440-24-6	Strontium from Strontium carbonate	330 mg/m3
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7440-09-7	Potassium from Potassium nitrate	150 mg/m3
7439-98-7	molybdenum	2,000 mg/m3
	Sodium from Sodium carbonate	870 mg/m3
	Lithium from Lithium carbonate	220 mg/m3
7440-24-6	Strontium from Strontium carbonate	2,000 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm

Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

(Contd. of page 3)

Printing date 09/21/2017 Reviewed on 09/21/2017

Product Name: Mixed Calibration Standard 2A

· Eye protection:



9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: According to product specification Characteristic · Odour Threshold: Not applicable. · pH-value: Not applicable. · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 83 °C (181 °F) · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Decomposition temperature: Not applicable. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Not applicable. Lower: Upper: Not applicable. 23 hPa (17 mm Hg) · Vapor pressure at 20 °C (68 °F): · Density at 20 °C (68 °F) 1.02653 g/cm3 (8.566 lbs/gal) Not applicable. · Relative density · Vapor density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not applicable. · Viscosity: Not applicable. Dynamic: Kinematic: Not applicable. · Solvent content: 0.0%Organic solvents: Water: · Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Product Name: Mixed Calibration Standard 2A

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- $\cdot \textit{\textbf{Mobility in soil}} \ \textit{No further relevant information available}.$
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

 ${\it Must not reach bodies of water or drainage ditch undiluted or unneutralized.}$

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

1 4 700			C	
14 Li	ranspo	rt uni	orma	nom

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3264

· UN proper shipping name

· DOT

· ADR · IMDG, IATA Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution)
3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution)
CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION)

(Contd. on page 6)

Product Name: Mixed Calibration Standard 2A

(Contd. of page 5) · Transport hazard class(es) $\cdot DOT$ · Class 8 Corrosive substances · Label · ADR, IMDG, IATA · Class 8 Corrosive substances · Label · Packing group · DOT, ADR, IMDG, IATA III · Environmental hazards: Not applicable. · Special precautions for user Warning: Corrosive substances · Danger code (Kemler): 80 · EMS Number: F-A,S-B· Segregation groups Acids· Stowage Category SW2 Clear of living quarters. · Stowage Code · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Not applicable. · Transport/Additional information: $\cdot ADR$ Code: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L

Code: E1

ACID SOLUTION), 8, III

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC

· UN "Model Regulation":

· Excepted quantities (EQ)

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

54.4
. Section 355 (extremely hazardous substances).

7697-37-2 nitric acid

15 Regulatory information

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

7439-93-2 Lithium from Lithium carbonate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 7)

Product Name: Mixed Calibration Standard 2A

(Contd. of page 6)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

7439-93-2 Lithium from Lithium carbonate

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

7439-98-7 molybdenum

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 09/21/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

1 Identification

- · Product identifier
- · Product Name: Mixed Calibration Standard 3A
- · Part Number: MIXSTD3A-100
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3Fire = 0

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Product Name: Mixed Calibration Standard 3A

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

_	· Dangerous components:		
7697-37-2	7697-37-2 nitric acid 5.0%		
· Chemical i	dentification of the substance/preparation		
7723-14-0	Phosphorus from Ammonium dihydrogenorthophosphate	0.01%	
	Vanadium from Ammonium trioxovanadate	0.002%	
7440-45-1	Cerium from Cerium(III) nitrate hexahydrate	0.002%	
7440-48-4	cobalt	0.002%	
7732-18-5	water, distilled, conductivity or of similar purity	94.984%	

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- $\cdot \textit{Suitable extinguishing agents: } \textit{Use fire fighting measures that suit the environment.}$
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- $\cdot \textit{Personal precautions}, \textit{protective equipment and emergency procedures} \ \textit{Wear protective equipment}. \ \textit{Keep unprotected persons away}.$
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- $\cdot \textit{Methods and material for containment and cleaning up:}$

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
7697-37-2 nitric acid		0.16 ppm
7723-14-0 Phosphorus from Amm	onium dihydrogenorthophosphate	0.27 mg/m ²
7440-62-2 Vanadium from Ammo	nium trioxovanadate	3 mg/m3
7440-45-1 Cerium from Cerium(I.	II) nitrate hexahydrate	30 mg/m3
7440-48-4 cobalt		0.18 mg/m²
PAC-2:		
7697-37-2 nitric acid		24 ppm
7723-14-0 Phosphorus from Amm	nonium dihydrogenorthophosphate	3 mg/m3
7440-62-2 Vanadium from Ammo	nium trioxovanadate	5.8 mg/m3
7440-45-1 Cerium from Cerium(I.	II) nitrate hexahydrate	330 mg/m ²
7440-48-4 cobalt		2 mg/m3

Product Name: Mixed Calibration Standard 3A

		(Contd. of page 2)
· PAC-3:		
7697-37-2	nitric acid	92 ppm
7723-14-0	Phosphorus from Ammonium dihydrogenorthophosphate	18 mg/m3
7440-62-2	Vanadium from Ammonium trioxovanadate	35 mg/m3
7440-45-1	Cerium from Cerium(III) nitrate hexahydrate	2,000 mg/m3
7440-48-4	cobalt	20 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

	· Components with	limit values that re	equire monitoring	g at the workplace:
--	-------------------	----------------------	-------------------	---------------------

7697-37-2 nitric acid PEL Long-term value: 5 mg/m³, 2 ppm PEL Short term value: 10 mg/m³, 4 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

(Contd. of page 3)

Printing date 09/21/2017 Reviewed on 09/21/2017

Product Name: Mixed Calibration Standard 3A

· Eye protection:



9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: According to product specification Characteristic · Odour Threshold: Not applicable. · pH-value: Not applicable. · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 83 °C (181 °F) · Flash point: Not applicable. · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Decomposition temperature: Not applicable. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Not applicable. Lower: Upper: Not applicable. 23 hPa (17 mm Hg) · Vapor pressure at 20 °C (68 °F): · Density at 20 °C (68 °F) 1.02566 g/cm3 (8.559 lbs/gal) Not applicable. · Relative density · Vapor density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not applicable. · Viscosity: Not applicable. Dynamic: Kinematic: Not applicable. · Solvent content:

10 Stability and reactivity

Organic solvents: Water: • Other information

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

0.0%

Product Name: Mixed Calibration Standard 3A

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
7440-48-4 cobalt	2B
· NTP (National Toxicology Program)	
7440-48-4 cobalt	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- $\cdot \textit{Mobility in soil} \ \textit{No further relevant information available}.$
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

 $Do \ not \ allow \ product \ to \ reach \ ground \ water, \ water \ course \ or \ sewage \ system.$

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR · IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) 3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION)

(Contd. on page 6)

Product Name: Mixed Calibration Standard 3A

	(Contd. of page
· Transport hazard class(es)	
· DOT	
U.V. Z	
CORROSIVE	
8	
· Class	8 Corrosive substances
· Label	8
· ADR, IMDG, IATA	
<u>, , , , , , , , , , , , , , , , , , , </u>	
8	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80 F-A,S-B
· EMS Number: · Segregation groups	r-A,S-B Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARP	
Code	Not applicable.
· Transport/Additional information:	
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	61
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1
· Excepteu quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per timer packaging. 30 m

15 Regulatory information

· UN "Model Regulation":

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}$
- · Sara

Section 355 (extremely hazardous substances): 7697-37-2 nitric acid 7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate Section 313 (Specific toxic chemical listings): 7697-37-2 nitric acid 7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate 7440-62-2 Vanadium from Ammonium trioxovanadate 7440-48-4 cobalt		
7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate Section 313 (Specific toxic chemical listings): 7697-37-2 nitric acid 7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate 7440-62-2 Vanadium from Ammonium trioxovanadate 7440-48-4 cobalt		
Section 313 (Specific toxic chemical listings): 7697-37-2 nitric acid 7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate 7440-62-2 Vanadium from Ammonium trioxovanadate 7440-48-4 cobalt	7697-37-2	nitric acid
7697-37-2 nitric acid 7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate 7440-62-2 Vanadium from Ammonium trioxovanadate 7440-48-4 cobalt	7723-14-0	Phosphorus from Ammonium dihydrogenorthophosphate
7723-14-0 Phosphorus from Ammonium dihydrogenorthophosphate 7440-62-2 Vanadium from Ammonium trioxovanadate 7440-48-4 cobalt	· Section 313	B (Specific toxic chemical listings):
7440-62-2 Vanadium from Ammonium trioxovanadate 7440-48-4 cobalt	7697-37-2	nitric acid
7440-48-4 cobalt	7723-14-0	Phosphorus from Ammonium dihydrogenorthophosphate
111111111111111111111111111111111111111	7440-62-2	Vanadium from Ammonium trioxovanadate
model (m. 1, o. 1, c., o., o., o., o., o., o., o., o., o., o	7440-48-4	cobalt
· TSCA (Toxic Substances Control Act):		

Maximum net quantity per outer packaging: 1000 ml

ACID SOLUTION), 8, III

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

7440-48-4 cobalt

(Contd. on page 7)

Product Name: Mixed Calibration Standard 3A

(Contd. of page 6)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

7440-48-4 cobalt

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 09/21/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

1 Identification

- · Product identifier
- · Product Name: Mixed Calibration Standard 4A
- · Part Number: MXSTD4A-100N
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Product Name: Mixed Calibration Standard 4A

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
7697-37-2	nitric acid	5.0%
· Chemical i	dentification of the substance/preparation	
7664-39-3	hydrofluoric acid	0.1%
7631-86-9	silicon dioxide, chemically prepared	0.01%
7429-90-5	aluminium	0.01%
7440-32-6	titanium	0.01%
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	0.005%
7440-66-6	zinc powder -zinc dust (stabilized)	0.005%
7440-31-5	tin	0.004%
7732-18-5	water, distilled, conductivity or of similar purity	94.856%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for Doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- $\cdot \textit{Suitable extinguishing agents: } \textit{Use fire fighting measures that suit the environment.}$
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

	*	
· PAC-1:		
7697-37-2	nitric acid	0.16 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m3
7440-32-6	titanium	30 mg/m3
	Chromium from Chromium(III) nitrate nonahydrate	1.5 mg/m3
7440-66-6	zinc powder -zinc dust (stabilized)	6 mg/m3
7440-31-5	tin	6 mg/m3
· PAC-2:		
7697-37-2	nitric acid	24 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m3
	(Cont.	d on nage 3

(Contd. on page 3)

Product Name: Mixed Calibration Standard 4A

		(Contd. of page 2)	
7440-32-6	titanium	330 mg/m3	
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	17 mg/m3	
7440-66-6	zinc powder -zinc dust (stabilized)	21 mg/m3	
7440-31-5	tin	67 mg/m3	
· PAC-3:	· PAC-3:		
7697-37-2	nitric acid	92 ppm	
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m3	
7440-32-6	titanium	2,000 mg/m3	
7440-47-3	Chromium from Chromium(III) nitrate nonahydrate	99 mg/m3	
7440-66-6	zinc powder -zinc dust (stabilized)	120 mg/m3	
7440-31-5	tin	400 mg/m3	

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- $\cdot \textit{Control parameters}$
- · Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm Long-term value: 5.2 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Product Name: Mixed Calibration Standard 4A

(Contd. of page 3)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

Odor: Characteristic
 Odour Threshold: Not applicable.
 pH-value: Not applicable.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:83 °C (181 °F)Flash point:Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not applicable.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

Not applicable.

· Explosion limits: Lower:

Upper: Not applicable.

• Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg)

• Density at 20 °C (68 °F) 1.01749 g/cm³ (8.491 lbs/gal)

Relative density
Vapor density
Evaporation rate
Not applicable.
Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

Organic solvents: 0.0 % Water: 94.9 %

• Other information No further relevant information available.

10 Stability and reactivity

- $\cdot \textit{Reactivity No further relevant information available}.$
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Product Name: Mixed Calibration Standard 4A

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
7631-86-9 silicon dioxide, chemically prepared	3
7440-47-3 Chromium from Chromium(III) nitrate nonahydrate	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textbf{\it Bioaccumulative potential} \ No \ further \ relevant \ information \ available.$
- · Mobility in soil No further relevant information available.
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- $\cdot \textit{Other adverse effects} \ \textit{No further relevant information available}.$

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	UN3264	
· UN proper shipping name · DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution, Hydrofluoric acid)	
· ADR	3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution, Hydrofluoric acid)	
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID SOLUTION, HYDROFLUORIC ACID)	

(Contd. on page 6)

Product Name: Mixed Calibration Standard 4A

(Contd. of page 5) · Transport hazard class(es) $\cdot DOT$ · Class 8 Corrosive substances · Label · ADR, IMDG, IATA 8 Corrosive substances · Class · Label · Packing group · DOT, ADR, IMDG, IATA III · Environmental hazards: Not applicable. · Special precautions for user Warning: Corrosive substances · Danger code (Kemler): 80 F-A,S-B· EMS Number: · Segregation groups Acids· Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Not applicable. · Transport/Additional information: $\cdot ADR$ Code: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml \cdot IMDG 5L · Limited quantities (LQ) · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC · UN "Model Regulation":

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara		
· Section 355 (extremely hazardous substances):		
7697-37-2 nitric acid		
7664-39-3 hydrofluoric acid		
· Section 313 (Specific toxic chemical listings):		
7697-37-2 nitric acid		
7664-39-3 hydrofluoric acid		
7429-90-5 aluminium		
7440-47-3 Chromium from Chromium(III) nitrate nonahydrate		
7440-66-6 zinc powder -zinc dust (stabilized)		
· TSCA (Toxic Substances Control Act):		
7697-37-2 nitric acid		
7631-86-9 silicon dioxide, chemically prepared		
7429-90-5 aluminium		

ACID SOLUTION, HYDROFLUORIC ACID), 8, III

Product Name: Mixed Calibration Standard 4A

(Contd. of page 6) 7440-32-6 titanium 7440-47-3 Chromium from Chromium(III) nitrate nonahydrate 7440-66-6 zinc powder -zinc dust (stabilized) 7440-31-5 tin 7732-18-5 water, distilled, conductivity or of similar purity

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7440-66-6 zinc powder -zinc dust (stabilized) D, I, II

· TLV (Threshold Limit Value established by ACGIH)

7429-90-5 aluminium A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

· Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

· Date of preparation / last revision 09/21/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/21/2017 Reviewed on 09/21/2017

Product Name: Mixed Calibration Standard 4A

NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. of page 7)

1 Identification

- · Product identifier
- · Product Name: Mixed Calibration Standard 5A
- · Part Number: MIXSTD5A-100
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Product Name: Mixed Calibration Standard 5A

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:		
7697-37-2	nitric acid	5.0%	
· Chemical i	· Chemical identification of the substance/preparation		
7439-89-6	iron	0.01%	
7439-92-1	Lead from Lead Oxide	0.01%	
7439-95-4	magnesium	0.01%	
7440-28-0	Thallium from Thallium nitrate	0.005%	
7440-02-0		0.002%	
7440-41-7	Beryllium from Beryllium Acetate	0.001%	
7732-18-5	water, distilled, conductivity or of similar purity	94.962%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for Doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- $\cdot \textit{Suitable extinguishing agents: } \textit{Use fire fighting measures that suit the environment.} \\$
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
7697-37-2 nitric acid	0.16 ppm
7439-89-6 iron	3.2 mg/m3
7439-92-1 Lead from Lead Oxide	0.15 mg/m3
7439-95-4 magnesium	18 mg/m3
7440-28-0 Thallium from Thallium nitrate	0.06 mg/m3
7440-02-0 nickel	4.5 mg/m3
7440-41-7 Beryllium from Beryllium Acetate	0.0023 mg/m
PAC-2:	
7697-37-2 nitric acid	24 ppm
7439-89-6 iron	35 mg/m3

Product Name: Mixed Calibration Standard 5A

		(Contd. of page 2)
7439-92-1 1	Lead from Lead Oxide	120 mg/m3
7439-95-4 n	nagnesium	200 mg/m3
7440-28-0 7	Thallium from Thallium nitrate	3.3 mg/m3
7440-02-0 r	nickel	50 mg/m3
7440-41-7 I	Beryllium from Beryllium Acetate	0.025 mg/m3
· PAC-3:		
7697-37-2 n	nitric acid	92 ppm
7439-89-6 i	ron	150 mg/m3
7439-92-1 1	Lead from Lead Oxide	700 mg/m3
7439-95-4 n	nagnesium	1,200 mg/m3
7440-28-0 T	Thallium from Thallium nitrate	20 mg/m3
7440-02-0 r	nickel	99 mg/m3
7440-41-7 I	Beryllium from Beryllium Acetate	0.1 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- $\cdot \textit{Control parameters}$
- · Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm
Long-term value: 5.2 mg/m³, 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- $\cdot \textit{General protective and hygienic measures:} \\$

 ${\it Keep \ away \ from \ foodstuffs, \ beverages \ and \ feed.}$

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Product Name: Mixed Calibration Standard 5A

(Contd. of page 3)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

· pH-value:

Form: Liquid

Color: According to product specification

Not applicable.

Odor: Characteristic
 Odour Threshold: Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 83 °C (181 °F)

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not applicable.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not applicable.Upper:Not applicable.

· Vapor pressure at 20 °C (68 °F): 23 hPa (17 mm Hg)

Density at 20 °C (68 °F)
 Relative density
 Vapor density
 Evaporation rate
 1.02765 g/cm³ (8.576 lbs/gal)
 Not applicable.
 Not applicable.
 Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not applicable.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

 Organic solvents:
 0.0 %

 Water:
 95.0 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 5)

Product Name: Mixed Calibration Standard 5A

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 4)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic categories

· Carcinogenic categories · IARC (International Agency for Research on Cancer)	
7439-92-1 Lead from Lead Oxide	2B
7440-02-0 nickel	2 <i>B</i>
7440-41-7 Beryllium from Beryllium Acetate	1
· NTP (National Toxicology Program)	
7439-92-1 Lead from Lead Oxide	R
7440-02-0 nickel	R
7440-41-7 Beryllium from Beryllium Acetate	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN3264
- · UN proper shipping name
- \cdot DOT Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution) $\cdot ADR$

3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid solution)

Product Name: Mixed Calibration Standard 5A

	(Contd. of page
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACIDIC)
· Transport hazard class(es)	
· DOT	
CORROSIVE	
Class Label	8 Corrosive substances 8
· ADR, IMDG, IATA	
· Class	8 Corrosive substances
Label	8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number: Segregation groups Stowage Category Stowage Code	Warning: Corrosive substances 80 F-A,S-B Acids A SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/	
Code	Not applicable.
Transport/Additional information:	
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRI ACID SOLUTION), 8, III

15 Regulatory information

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture} \\$

· Sara			
· Section 355	· Section 355 (extremely hazardous substances):		
7697-37-2	nitric acid		
	· Section 313 (Specific toxic chemical listings):		
7697-37-2	nitric acid		
	Lead from Lead Oxide		
7440-28-0	Thallium from Thallium nitrate		
7440-02-0 i	nickel		
7440-41-7	Beryllium from Beryllium Acetate		
· TSCA (Toxi	· TSCA (Toxic Substances Control Act):		

All ingredients are listed.

(Contd. on page 7)

Product Name: Mixed Calibration Standard 5A

· Proposition 65

(Contd. of page 6)

F
· Chemicals known to cause cancer:
7439-92-1 Lead from Lead Oxide
7440-02-0 nickel
7440-41-7 Beryllium from Beryllium Acetate
Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
7439-92-1 Lead from Lead Oxide	B2	
7440-41-7 Beryllium from Beryllium Acetate	B1, K/L(inh), CBD(oral)	
· TLV (Threshold Limit Value established by ACGIH)		
7439-92-1 Lead from Lead Oxide	A3	
7440-02-0 nickel	A5	
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
7440-02-0 nickel		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Danger
- · Hazard-determining components of labeling:

nitric acid

- · Hazard statements
- H314 Causes severe skin burns and eye damage.
- · Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 09/21/2017 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/21/2017 Reviewed on 09/21/2017

Product Name: Mixed Calibration Standard 5A

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. of page 7)