1 Identification

- · Product identifier
- · Product Name: 1000 ug/g Arsenic in Base Oil 75
- · Part Number: ORG-AS8-2Z
- $\cdot \textbf{\textit{Application of the substance / the mixture } \textit{Certified Reference Material} \\$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

arsenic

- · Hazard statements
- H350 May cause cancer.
- · Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *0 Fire = 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

Product Name: 1000 ug/g Arsenic in Base Oil 75

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

7440-38-2 arsenic

0.1%

· Chemical identification of the substance/preparation

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

99.9%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- $\cdot \textit{Personal precautions, protective equipment and emergency procedures} \ \textit{Not required}.$
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

Trouveure Tenen Crucium or Chemicum	
· PAC-1:	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	140 mg/m^3
7440-38-2 arsenic	1.5 mg/m ³
· PAC-2:	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	$1,500 \text{ mg/m}^3$
7440-38-2 arsenic	17 mg/m³
· PAC-3:	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	$8,900 \text{ mg/m}^3$
7440-38-2 arsenic	100 mg/m^3

7 Handling and storage

- · Handling:
- $\cdot \textit{Precautions for safe handling}$

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- $\cdot \textit{Conditions for safe storage, including any incompatibilities}$
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/26/2019 Reviewed on 06/26/2019

Product Name: 1000 ug/g Arsenic in Base Oil 75

(Contd. of page 2)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7440-38-2 arsenic

PEL Long-term value: 0.5* 0.01** mg/m3

as As; *organic**inorg. compds.; 29 CFR 1910.1018

REL Ceiling limit value: 0.002 mg/m³

as As; 15min; See Pocket Guide App. A

TLV Long-term value: 0.01 mg/m³ as As; BEI

· Ingredients with biological limit values:

7440-38-2 arsenic

BEI 35 μg As/L

Medium: urine

Time: end of workweek

Parameter: Inorganic arsenic plus methylated metabolites (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

· Odor: Characteristic

(Contd. on page 4)

Product Name: 1000 ug/g Arsenic in Base Oil 75

		(Contd. of page 3		
· Odour Threshold:	Not applicable.			
· pH-value:	Not applicable.			
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.			
· Flash point:	Not applicable.			
· Flammability (solid, gaseous):	Not applicable.			
· Decomposition temperature:	Not applicable.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits: Lower: Upper:	Not applicable. Not applicable.			
· Vapor pressure:	Not determined.			
 Density Relative density Vapor density Evaporation rate 	Relative density Not applicable. Vapor density Not applicable.			
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/wa	er): Not applicable.			
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.			
· Solvent content: VOC content:	0.00 %			
Solids content: · Other information	0.1% No further relevant information available.			

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot \textit{Conditions to avoid No further relevant information available}.$
- · Incompatible materials: No further relevant information available.
- $\cdot \textit{Hazardous decomposition products:} \ \textit{No dangerous decomposition products known.}$

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
7440-38-2 arsenic	1

· NTP (National Toxicology Program)

7440-38-2 arsenic

· OSHA-Ca (Occupational Safety & Health Administration)

7440-38-2 arsenic

K

Product Name: 1000 ug/g Arsenic in Base Oil 75

(Contd. of page 4)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	100				C	
1/4		rans	nori	7111	forma	non

· DOT, ADR, ADN, IMDG, IATA

Not Regulated

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA

Not Regulated

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Not Regulated

· Packing group

· DOT, ADR, IMDG, IATA Not Regulated

· Environmental hazards: Not applicable.

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC

C**ode** Not applicable.

UN "Model Regulation": Not Regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 313 (Specific toxic chemical listings):

7440-38-2 arsenic

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

7440-38-2 arsenic

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 6)

Product Name: 1000 ug/g Arsenic in Base Oil 75

(Contd. of page 5)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7440-38-2 arsenic

A

· TLV (Threshold Limit Value established by ACGIH)

7440-38-2 arsenic

A 1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

7440-38-2 arsenic

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

arsenic

Hazard statements

H350 May cause cancer.

· Precautionary statements

Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

- · Date of preparation / last revision 06/26/2019 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Carc. 1A: Carcinogenicity – Category 1A