Page 1/6

# **1 Identification**

- · Product identifier
- · Product Name: 5000 ug/g Chromium in Base Oil 75
- · Part Number: ORG-CR8-4Z
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
   Manufacturer/Supplier:
   SPEX CertiPrep, LLC.
   203 Norcross Ave, Metuchen,
   NJ 08840 USA
- Information department: product safety department • Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887
- 2 Hazard(s) identification
- · Classification of the substance or mixture
- Eye Irrit. 2B H320 Causes eye irritation.
- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Not Regulated
- · Signal word Warning
- · Hazard statements
- H320 Causes eye irritation.
- · Precautionary statements
- Wash thoroughly after handling.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

 HEALTH
 1
 Health = 1

 FIRE
 0
 Fire = 0

 REACTIVITY
 0
 Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components: Not Regulated
- · Chemical identification of the substance/preparation

64742-65-0 Distillates (petr	oleum), solvent-dewaxed heavy paraffinic	99.5%
7440-47-3 Chromium from	n Chromium(III) nitrate nonahydrate	0.5%
	· · · · · · · · · · · · · · · · · · ·	

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

Reviewed on 09/21/2017

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/21/2017

#### Product Name: 5000 ug/g Chromium in Base Oil 75

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 7 for information on safe hundring.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

# · Protective Action Criteria for Chemicals

· PAC-1:	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	140 mg/m3
7440-47-3 Chromium from Chromium(III) nitrate nonahydrate	1.5 mg/m3
· PAC-2:	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	1,500 mg/m3
7440-47-3 Chromium from Chromium(III) nitrate nonahydrate	17 mg/m3
· PAC-3:	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	8,900 mg/m3
7440-47-3 Chromium from Chromium(III) nitrate nonahydrate	99 mg/m3

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- $\cdot$  Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing.

(Contd. on page 3)

US

US

Safety Data Sheet acc. to OSHA HCS

Printing date 09/21/2017

#### Product Name: 5000 ug/g Chromium in Base Oil 75

(Contd. of page 2)

Reviewed on 09/21/2017

Wash hands before breaks and at the end of work.

- Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection: Goggles recommended during refilling.

## 9 Physical and chemical properties

Information on basic physical and chemical properties		
· General Information		
· Appearance: Form:	Liquid	
Form: Color:	Liquid According to product specification	
· Odor:	<i>Characteristic</i>	
· Odour Threshold:	Not applicable.	
· pH-value:	Not applicable.	
•		
· Change in condition		
Melting point/Melting range:	Undetermined.	
<b>Boiling point/Boiling range:</b>	Undetermined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not applicable.	
· Auto igniting:	Product is not selfigniting.	
• Danger of explosion:	Product does not present an explosion hazard.	
• Explosion limits:		
Lower:	Not applicable.	
Upper:	Not applicable.	
· Vapor pressure:	Not determined.	
· Density	Not applicable.	
· Relative density	Not applicable.	
· Vapor density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water	r): Not applicable.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
	(Contd. on page 4)	

3

Safety Data Sheet acc. to OSHA HCS

Printing date 09/21/2017

Product Name: 5000 ug/g Chromium in Base Oil 75

· Other information

No further relevant information available.

**10 Stability and reactivity** 

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7440-47-3 Chromium from Chromium(III) nitrate nonahydrate

## · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	Not Regulated	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not Regulated	
		(Contd. on page 5)

Reviewed on 09/21/2017

Safety Data Sheet acc. to OSHA HCS

*Printing date 09/21/2017* 

Reviewed on 09/21/2017

Product Name: 5000 ug/g Chromium in Base Oil 75

		(Contd. of page 4)
· Transport hazard class(es)		
· DOT, ADR, IMDG, IATA · Class	Not Regulated	
· Packing group · DOT, ADR, IMDG, IATA	Not Regulated	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
• Transport in bulk according to Annex II of MARPO Code	L73/78 and the IBC Not applicable.	
· UN "Model Regulation":	Not Regulated	

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara	
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
7440-47-3 Chromium from Chromium(III) nitrate nonahydrate	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
·NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).	
Hazard pictograms Not Regulated	
· Signal word Warning	
• Hazard statements H320 Causes eve irritation.	
11520 Gauses eye irritation.	

· Precautionary statements

Wash thoroughly after handling.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

· Contact:

SPEX CertiPrep, LLC.

1-732-549-7144

· Date of preparation / last revision 09/21/2017 / -

US

Printing date 09/21/2017

### Product Name: 5000 ug/g Chromium in Base Oil 75

Abbreviations and acronyms:
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transport Association
 ACGH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLY: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Exposure Limit
 Exposure Limit
 Exposure Limit
 Ey Firit. 2B: Serious cye damage/eye irritation – Category 2B

Reviewed on 09/21/2017