

Page 1/8

Reviewed on 06/09/2023

# 1 Identification

- · Product identifier
- · Product Name: <u>Aroclor 1254 (High Level)</u>
- · Part Name: PCB-1254H
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
   Manufacturer/Supplier:
   Spex CertiPrep, LLC.
   203 Norcross Ave, Metuchen,
   NJ 08840 USA
   732-549-7144
   USMet-CRMSales@antylia.com
- Information department: product safety department • Emergency telephone number:
- Emergency Phone Number (24 hours)
- CHEMTREC (800-424-9300) Outside US: 703-527-3887

# 2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 2

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.



GHS08 Health hazard

Carcinogenicity 1BH350 May cause cancer.Toxic to Reproduction 2H361 Suspected of damaging fertility or the unborn child.Specific Target Organ Toxicity - Repeated Exposure 2H373 May cause damage to organs through prolonged or repeated exposure.Aspiration Hazard 1H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.



Skin Irritation 2

Specific Target Organ Toxicity - Single Exposure 3

· Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: n-hexane Aroclor 1254
- · Hazard statements
- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H350 May cause cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H304 May be fatal if swallowed and enters airways.
- · Precautionary statements
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.



### Product Name: Aroclor 1254 (High Level)

Reviewed on 06/09/2023

P260 Do not breathe dust/fume/gas/mist/vapors/sprav. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 If swallowed: Immediately call a poison center/doctor. P321 Specific treatment (see on this label). P331 Do NOT induce vomiting. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a poison center/doctor if you feel unwell. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. P501 · Classification system:

Safety Data Sheet acc. to OSHA HCS

## · NFPA ratings (scale 0 - 4)



# · HMIS-ratings (scale 0 - 4)



#### · Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	omponents:	
110-54-3	n-hexane	99.9%
11097-69-1	Aroclor 1254	0.1%

## 4 First-aid measures

## · Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

- $\cdot$  Personal precautions, protective equipment and emergency procedures
- Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.

 $<sup>\</sup>cdot \textit{Environmental precautions: } \textit{Do not allow to enter sewers/ surface or ground water.}$ 

# Product Name: Aroclor 1254 (High Level)

Page 3/8

Safety Data Sheet acc. to OSHA HCS

Reviewed on 06/09/2023

•	Methods	and	material j	for	containment	and	cleaning	up:
---	---------	-----	------------	-----	-------------	-----	----------	-----

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

# See Section 13 for disposal information.

## Protective Action Criteria for Chemicals

· PAC-2:       110-54-3       n-hexane       2900* ppm         11097-69-1       Aroclor 1254       68 mg/m <sup>3</sup> · PAC-3:       110-54-3       n-hexane         110-54-3       n-hexane       8600** ppm	· PAC-1:	
· PAC-2:       110-54-3       n-hexane       2900* ppm         11097-69-1       Aroclor 1254       68 mg/m³         · PAC-3:       110-54-3       n-hexane         110-54-3       n-hexane       8600** ppm	110-54-3 n-hexane	260 ppm
110-54-3       n-hexane       2900* ppm         11097-69-1       Aroclor 1254       68 mg/m <sup>3</sup> • PAC-3:       110-54-3       n-hexane         110-54-3       n-hexane       8600** ppm	11097-69-1 Aroclor 1254	1.5 mg/m <sup>3</sup>
11097-69-1     Aroclor 1254     68 mg/m <sup>3</sup> • PAC-3:     110-54-3     n-hexane	· PAC-2:	
• <b>PAC-3:</b> 110-54-3 n-hexane 8600** ppm		
110-54-3 n-hexane 8600** ppm	11097-69-1 Aroclor 1254	68 mg/m³
	110-54-3 n-hexane 86	600** ppm
11097-69-1 Aroclor 1254 200 mg/m <sup>3</sup>	11097-69-1 Aroclor 1254 20	00 mg/m <sup>3</sup>

# 7 Handling and storage

## · Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information accurate the provided of the provided
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities • Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

· Additional information	about design	of technical	systems: N	o further	data: see item 7.
1 Idamonal myor marion	about acoign	oj recimicar i	systemest it	o juniter .	actively bee them it

## Control parameters

· Cont	<i>rol parameters</i>				
· Com	· Components with limit values that require monitoring at the workplace:				
110	54-3 n-hexane				
PEL	Long-term value: 1800 mg/m <sup>3</sup> , 500 ppm				
REL	Long-term value: 180 mg/m <sup>3</sup> , 50 ppm				
TLV	Long-term value: 50 ppm				
	Skin; BEI				
1109	7-69-1 Aroclor 1254				
PEL	Long-term value: 0.5 mg/m <sup>3</sup>				
	Skin				
REL	Long-term value: 0.001 mg/m <sup>3</sup>				
	See Pocket Guide App. A				
TLV	Long-term value: 0.5 mg/m <sup>3</sup> Skin, A3				
	edients with biological limit values:				
110	54-3 n-hexane				
	0.5 mg/L				
	Medium: urine				
	Time: end of shift Parameter: 2.5-Hexanedione without hydrolysis				
· Aaai	tional information: The lists that were valid during the creation were used as basis.				

Safety Data Sheet acc. to OSHA HCS

Reviewed on 06/09/2023

Printing date 06/09/2023

## Product Name: Aroclor 1254 (High Level)

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

<ul> <li>Information on basic physical and o</li> <li>General Information</li> </ul>	chemical properties
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odour Threshold:	Not applicable.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	69 °C (156.2 °F)
· Flash point:	< 0 °C (< 32 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Ignition temperature:	240 °C (464 °F)
• Decomposition temperature:	Not applicable.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.4 Vol %
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
· Density at 20 °C (68 °F)	0.66 g/cm <sup>3</sup> (5.5077 lbs/gal)
· Relative density	Not applicable.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	ar). Not applicable



<sup>(</sup>Contd. of page 3)



#### Product Name: Aroclor 1254 (High Level)

Page 5/8

(Contd.	of page 4)
---------	------------

		10
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Organic solvents:	99.9 %	
VOC content:	99.90 %	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot$  Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- $\cdot \textit{Additional toxicological information:}$
- The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant Product is suspected to cause damage to fertility.

Product is suspected to cause birth defects.

## · Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
11097-69-1 Aroclor 1254	2A
· NTP (National Toxicology Program)	
11097-69-1 Aroclor 1254	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water
- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

· Waste treatment methods

• Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.



# Product Name: Aroclor 1254 (High Level)

• Uncleaned packagings: • Recommendation: Disposal must be made according to official regulations.

(Contd. of page 5)

Transport information	
UN-Number DOT, ADR, IMDG, IATA	UN1208
UN proper shipping name	
DOT ADR	Hexanes 1208 HEXANES, ENVIRONMENTALLY HAZARDOUS
ADK IMDG, IATA	HEXANES
Transport hazard class(es)	
DOT	
RANNER & LID	
Class Label	3 Flammable liquids 3
ADR	
Class Label	3 Flammable liquids 3
IMDG, IATA	
Class Label	3 Flammable liquids
Label	3 Flammable liquids 3
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards:	3 11
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR):	3 II Symbol (fish and tree)
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user	3 II Symbol (fish and tree) Warning: Flammable liquids
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR):	3 II Symbol (fish and tree)
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number:	3 II Symbol (fish and tree) Warning: Flammable liquids 33
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code):	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable.
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information:	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable. Code: E2
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable.
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable. Code: E2 Maximum net quantity per inner packaging: 30 ml
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR Excepted quantities (EQ)	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable. Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml IL
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR Excepted quantities (EQ)	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable. Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml IL Code: E2
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR Excepted quantities (EQ) IMDG Limited quantities (LQ)	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable. Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml IL Code: E2 Maximum net quantity per inner packaging: 30 ml
Label Packing group DOT, ADR, IMDG, IATA Environmental hazards: Special marking (ADR): Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Transport in bulk according to Annex II of MARPOL73/78 and Transport/Additional information: ADR Excepted quantities (EQ) IMDG Limited quantities (LQ)	3 II Symbol (fish and tree) Warning: Flammable liquids 33 F-E,S-D E d the IBC Code Not applicable. Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml IL Code: E2

Safety Data Sheet acc. to OSHA HCS

### Product Name: Aroclor 1254 (High Level)

Page 7/8

(Contd. of page 6)

15 Regulatory information	ulatory information
---------------------------	---------------------

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara	
· Section 313 (Specific toxic chemical listings):	
110-54-3 n-hexane	
· TSCA (Toxic Substances Control Act):	
110-54-3 n-hexane	ACTIVE
· Hazardous Air Pollutants	
110-54-3 n-hexane	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
110-54-3 n-hexane	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
110-54-3 n-hexane	11
11097-69-1 Aroclor 1254	B2
· TLV (Threshold Limit Value)	

11097-69-1 Aroclor 1254

• NIOSH-Ca (National Institute for Occupational Safety and Health)

## 11097-69-1 Aroclor 1254

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling:
- n-hexane
- Aroclor 1254
- Hazard statements
- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation. H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

•	· Precautionary statements		
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
	P240	Ground/bond container and receiving equipment.	
	P241	Use explosion-proof electrical/ventilating/lighting/equipment.	
	P260	Do not breathe dust/fume/gas/mist/vapors/spray.	
	P280	Wear protective gloves/protective clothing/eye protection/face protection.	
	P301+P310	If swallowed: Immediately call a poison center/doctor.	
	P321	Specific treatment (see on this label).	
	P331	Do NOT induce vomiting.	
	P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	P312	Call a poison center/doctor if you feel unwell.	
	P362+P364	Take off contaminated clothing and wash it before reuse.	
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
	P405	Store locked up.	

A3



Safety Data Sheet acc. to OSHA HCS

Printing date 06/09/2023

## Product Name: Aroclor 1254 (High Level)

(Contd. of page 7)

Page 8/8

US —

Reviewed on 06/09/2023

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact:
- Spex CertiPrep, LLC. 1-732-549-7144
- · Date of preparation / last revision 06/09/2023

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids Category 2
- Skin Irritation 2: Skin corrosion/irritation Category 2
- Carcinogenicity 1B: Carcinogenicity Category 1B Toxic to Reproduction 2: Reproductive toxicity Category 2
- Specific Target Organ Toxicity Single Exposure 3: Specific target organ toxicity (single exposure) Category 3 Specific Target Organ Toxicity Repeated Exposure 2: Specific target organ toxicity (repeated exposure) Category 2
- Aspiration Hazard 1: Aspiration hazard Category 1