Printing date 09/12/2023 Reviewed on 09/12/2023

1 Identification

· Product identifier

· Product Name: Spike Sample Standard I

· Part Name:

SPIKE-1 SPIKE-1-500

· Application of the substance / the mixture For Laboratory Use Only

· Uses advised against Not for Human or Animal Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Spex CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

732-549-7144

USMet-CRMSales@antylia.com

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS05

· Signal word Danger

· Hazard-determining components of labeling:

nitric acid

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 0Reactivity = 0



Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:	
7697-37-2 nitric acid	5.0%
7664-39-3 hydrofluoric acid	0.1%
Chemical identification of the substance/preparation	
7732-18-5 water, distilled, conductivity or of similar purity	94.599%
87-69-4 (+)-tartaric acid	0.15%
7429-90-5 aluminium	0.02%
7440-28-0 thallium	0.02%
7440-38-2 arsenic	0.02%
7440-39-3 barium	0.02%
7782-49-2 selenium	0.02%
7439-89-6 iron	0.01%
7439-92-1 lead	0.005%
7439-96-5 manganese	0.005%
7440-02-0 nickel	0.005%
7440-36-0 antimony	0.005%
7440-48-4 cobalt	0.005%
7440-62-2 vanadium	0.005%
7440-66-6 zinc powder- zinc dust (pyrophoric)	0.005%
7440-50-8 copper	0.0025%
7440-47-3 chromium	0.002%
7440-22-4 silver	0.0005%
7440-41-7 beryllium	0.0005%
7440-43-9 cadmium	0.0005%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not give anything to eat or drink Do not induce vomitting
- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- $\cdot \textit{Special hazards arising from the substance or mixture } \textit{During heating or in case of fire poisonous gases are produced.} \\$
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

(Contd. on page 3)



Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
7697-37-2 nitric acid	0.16 ppm
87-69-4 (+)-tartaric acid	1.6 mg/m³
7664-39-3 hydrofluoric acid	1.0 ppm
7440-28-0 thallium	0.06 mg/m^3
7440-38-2 arsenic	$1.5 mg/m^3$
7440-39-3 barium	$1.5 mg/m^3$
7782-49-2 selenium	0.6 mg/m^3
7439-89-6 iron	3.2 mg/m^3
7439-92-1 lead	0.15 mg/m^3
7439-96-5 manganese	3 mg/m ³
7440-02-0 nickel	4.5 mg/m^3
7440-36-0 antimony	1.5 mg/m^3
7440-48-4 cobalt	0.18 mg/m^3
7440-62-2 vanadium	3 mg/m ³
7440-50-8 copper	$3 mg/m^3$
7440-47-3 chromium	1.5 mg/m^3
7440-22-4 silver	0.3 mg/m^3
7440-41-7 beryllium	0.0023 mg/m
7440-43-9 cadmium	0.10 mg/m^3
PAC-2:	
7697-37-2 nitric acid	24 ppm
87-69-4 (+)-tartaric acid	17 mg/m³
7664-39-3 hydrofluoric acid	24 ppm
7440-28-0 thallium	3.3 mg/m^3
7440-38-2 arsenic	17 mg/m³
7440-39-3 barium	180 mg/m³
7782-49-2 selenium	6.6 mg/m^3
7439-89-6 iron	35 mg/m ³
7439-92-1 lead	120 mg/m³
7439-96-5 manganese	5 mg/m ³
7440-02-0 nickel	50 mg/m^3
7440-36-0 antimony	13 mg/m³
7440-48-4 cobalt	$2 mg/m^3$
7440-62-2 vanadium	5.8 mg/m^3
7440-50-8 copper	33 mg/m ³
7440-47-3 chromium	17 mg/m^3
7440-22-4 silver	170 mg/m^3
7440-41-7 beryllium	0.025 mg/m
7440-43-9 cadmium	0.76 mg/m^3
	(Contd. on page 4



Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 3)

	,	
• PAC-3:		
7697-37-2	nitric acid	92 ppm
	(+)-tartaric acid	100 mg/m³
7664-39-3	hydrofluoric acid	44 ppm
7440-28-0	thallium	20 mg/m³
7440-38-2	arsenic	100 mg/m³
7440-39-3	barium	1,100 mg/m ³
7782-49-2	selenium	40 mg/m ³
7439-89-6	iron	150 mg/m³
7439-92-1		700 mg/m³
7439-96-5	manganese	1,800 mg/m ³
7440-02-0		99 mg/m³
7440-36-0	antimony	80 mg/m³
7440-48-4	cobalt	20 mg/m³
7440-62-2		35 mg/m ³
7440-50-8	copper	200 mg/m³
7440-47-3	chromium	99 mg/m³
7440-22-4		990 mg/m³
7440-41-7	beryllium	0.1 mg/m ³
7440-43-9	cadmium	4.7 mg/m³
		-

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- $\cdot \textbf{\textit{Additional information about design of technical systems:}} \ No \ further \ data; \ see \ section \ 7.$
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

7664-39-3 hydrofluoric acid

PEL Long-term value: 1* mg/m³, 3 ppm

as F, *sulfuric acid

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5* mg/m³, 6* ppm

*15-min, as F

TLV Long-term value: 0.5 ppm Ceiling limit value: 2 ppm

as F; Skin, BEI

· Ingredients with biological limit values:

7664-39-3 hydrofluoric acid

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine Medium: urine Time: end of shift

Parameter: Fluorides (background, nonspecific)

Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 4)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on	basic physic	cal and cl	hemical	properties
------------------	--------------	------------	---------	------------

· General Information

· Appearance:

Form: Liquid

Color: According to product specification

· Odor: Characteristic · Odour Threshold: Not applicable.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.
83 °C (181.4 °F)

Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not applicable.

• Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not applicable.
Upper: Not applicable.

• Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

• **Density at 20** °**C** (68 °**F**) 1.0249 g/cm³ (8.55279 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not applicable.
 Not applicable.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not applicable.

(Contd. on page 6)

Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 5)

		(Conta. or page 3)
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
Water:	94.6 %	
VOC content:	0.00 %	
Solids content:	0.3 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7697-37-2 nitric acid

Inhalative LC50/4 h 2.65 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive Irritant

· Carcinogenic categories

Curcinoge	nic cutegories	
· IARC (Inte	ernational Agency for Research on Cancer)	
7440-38-2	arsenic	1
7782-49-2	selenium	3
7439-92-1	lead	2B
7440-02-0	nickel	2B
7440-48-4	cobalt	2B
7440-47-3	chromium	3
7440-41-7	beryllium	1
7440-43-9	cadmium	1
· NTP (Nati	onal Toxicology Program)	$\overline{}$
7440-38-2	arsenic	K
7439-92-1	lead	R
7440-02-0	nickel	R
7440-48-4	cobalt	R
7440-41-7	beryllium	K
7440-43-9	cadmium	K
· OSHA-Ca	(Occupational Safety & Health Administration)	
7440-38-2	arsenic	
7440-43-9	cadmium	

(Contd. on page 7)

Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN3264
· UN proper shipping name · DOT · ADR · IMDG, IATA	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid) 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

- · Transport hazard class(es)
- $\cdot DOT$



· Class· Label8 Corrosive substances8

· ADR, IMDG, IATA



· Segregation Code

· Class

· Label	8	
· Packing group · DOT, ADR, IMDG, IATA	III	
· Environmental hazards:	Not applicable.	
· Special precautions for user · Hazard identification number (Kemler code):	Warning: Corrosive substances 80	
· EMS Number:	F- A , S - B	
· Segregation groups	(SGG1) Acids	
· Stowage Category	A	
· Stowage Code	SW2 Clear of living quarters.	

8 Corrosive substances

 $SG36\ Stow\ "separated\ from"\ SGG18-alkalis.$

SG49 Stow "separated from" SGG6-cyanides

(Contd. on page 8)



Reviewed on 09/12/2023 Printing date 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 7) · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: \cdot ADR · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml \cdot IMDG 5L· Limited quantities (LQ) · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

8, III

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID),

15 Regulatory information

 \cdot UN "Model Regulation":

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Car	

Sara	
Section 313 (Specific toxic chemical listings):	
7697-37-2 nitric acid	
7664-39-3 hydrofluoric acid	
7429-90-5 aluminium	
7440-28-0 thallium	
7440-38-2 arsenic	
7440-39-3 barium	
7782-49-2 selenium	
7439-92-1 lead	
7439-96-5 manganese	
7440-02-0 nickel	
7440-36-0 antimony	
7440-48-4 cobalt	
7440-62-2 vanadium	
7440-66-6 zinc powder- zinc dust (pyrophoric)	
7440-50-8 copper	
7440-47-3 chromium	
7440-22-4 silver	
7440-41-7 beryllium	
7440-43-9 cadmium	
TSCA (Toxic Substances Control Act):	
7732-18-5 water, distilled, conductivity or of similar purity	ACTIVE
7697-37-2 nitric acid	ACTIVE
87-69-4 (+)-tartaric acid	ACTIVE
7664-39-3 hydrofluoric acid	ACTIVE
7429-90-5 aluminium	ACTIVE
7440-28-0 thallium	ACTIVE
7440-38-2 arsenic	ACTIVE
7440-39-3 barium	ACTIVE
7782-49-2 selenium	ACTIVE
7439-89-6 iron	ACTIVE
7439-92-1 lead	ACTIVE
7439-96-5 manganese	ACTIVE
7440-02-0 nickel	ACTIVE
7440-36-0 antimony	ACTIVE
7440-48-4 cobalt	ACTIVE
7440-62-2 vanadium	ACTIVE
7440-50-8 copper	ACTIVE
7440-47-3 chromium	ACTIVE
	(Contd. on page 9
7440-02-0 nickel 7440-36-0 antimony 7440-48-4 cobalt 7440-62-2 vanadium 7440-50-8 copper	Ac A

Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

		ontd. of page 8)
7440-22-4	silver	ACTIVE
7440-41-7	beryllium	ACTIVE
7440-43-9	cadmium	ACTIVE
-	S Air Pollutants	
7664-39-3	hydrofluoric acid	
7439-92-1	lead	
7439-96-5	manganese	
7440-48-4	cobalt	
· Proposition	n 65	
· Chemicals	known to cause cancer:	
7440-38-2	arsenic	
7439-92-1	lead	
7440-02-0	nickel	
7440-48-4	cobalt	

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

7440-43-9 cadmium

7440-41-7 beryllium 7440-43-9 cadmium

· Chemicals known to cause developmental toxicity:

7440-43-9 cadmium

· Carcinogenic categories

· EPA (Env	· EPA (Environmental Protection Agency)		
7440-38-2	arsenic	A	
7440-39-3	barium	D, CBD(inh), NL(oral)	
7782-49-2	selenium	D	
7439-92-1	lead	B2	
7439-96-5	manganese	D	
7440-66-6	zinc powder- zinc dust (pyrophoric)	II	
7440-50-8	copper	D	
7440-22-4	silver	D	
7440-41-7	beryllium	B1, K/L(inh), CBD(oral)	
7440-43-9	cadmium	B1	

· TLV (Threshold Limit Value)		
7429-90-5	aluminium	A4
7440-38-2	arsenic	A1
7440-39-3	barium	A4
7439-92-1	lead	<i>A3</i>
7440-02-0	nickel	A5
7440-48-4	cobalt	<i>A3</i>
7440-43-9	cadmium	A2

· NIOSH-Ca	(National Institute for Occupational Safety and Health)
7440-38-2	arsenic
7440-02-0	nickel
7440-43-9	cadmium

[·] GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

[·] Hazard pictograms



GHS05

· Hazard-determining components of labeling:

nitric acid

[·] Signal word Danger



Printing date 09/12/2023 Reviewed on 09/12/2023

Product Name: Spike Sample Standard I

(Contd. of page 9)

· Hazard statements

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P260 Do not breathe dusts or mists. Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor. P310 P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

Spex CertiPrep, LLC. 1-732-549-7144

· Date of preparation / last revision 09/12/2023

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Eye Damage 1: Serious eye damage/eye irritation – Category 1