

Safety Data Sheet acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

1 Identification

- **Product identifier**
- **Trade name:** UST-360
- **Other means of identification**
- **Application of the substance / the mixture** For Laboratory Use Only
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
NSI Lab Solutions
7212 ACC Blvd.,
Raleigh, NC 27617
USA
- **Information department:** Product safety department
- **Emergency telephone number:** During normal opening times: +1 (919) 789-3000

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute toxicity - inhalation 3

H331 Toxic if inhaled.



GHS08 Health hazard

Germ cell mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1A

H350 May cause cancer.

Reproductive toxicity 2

H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) 1

H370 Causes damage to the central nervous system and the visual organs.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS06



GHS08

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 1)

· **Signal word** *Danger*· **Hazard-determining components of labeling:**

methanol
benzene
toluene
ethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.
Toxic if inhaled.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to the central nervous system and the visual organs.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Ground / bond container and receiving equipment.
Use explosion-proof [electrical/ventilating/lighting] equipment.
Use non-sparking tools.
Take action to prevent static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Specific treatment (see on this label).
If exposed or concerned: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Information pertaining to particular dangers for man and environment:**· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Classification according to (d)(1)(ii) of § 1910.1200**

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 2)

· **Hazards not otherwise classified**

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

* 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-56-1	methanol	80–100%
71-43-2	benzene	≤0.1%
91-20-3	naphthalene	≤0.1%
100-41-4	ethylbenzene	≤0.1%
108-88-3	toluene	≤0.1%

· **Non-hazardous components**

95-47-6	o-xylene	≤0.1%
95-63-6	1,2,4-trimethylbenzene	≤0.1%
106-42-3	p-xylene	≤0.1%
108-38-3	m-xylene	≤0.1%
108-67-8	mesitylene	≤0.1%
1634-04-4	tert-butyl methyl ether	≤0.1%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
67-56-1	methanol	530 ppm
71-43-2	benzene	52 ppm
91-20-3	naphthalene	15 ppm
95-63-6	1,2,4-trimethylbenzene	140 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
108-67-8	mesitylene	140 ppm
108-88-3	toluene	67 ppm
1634-04-4	tert-butyl methyl ether	50 ppm
· PAC-2:		
67-56-1	methanol	2100 ppm
71-43-2	benzene	800 ppm
91-20-3	naphthalene	83 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
100-41-4	ethylbenzene	1100 ppm
108-38-3	m-xylene	920 ppm
108-67-8	mesitylene	360 ppm
108-88-3	toluene	560 ppm
1634-04-4	tert-butyl methyl ether	570 ppm
· PAC-3:		
67-56-1	methanol	7200 ppm
71-43-2	benzene	4000* ppm
91-20-3	naphthalene	500 ppm
95-63-6	1,2,4-trimethylbenzene	470 ppm
100-41-4	ethylbenzene	1800 ppm
108-38-3	m-xylene	2500* ppm
108-67-8	mesitylene	470 ppm
108-88-3	toluene	3700 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 4)

1634-04-4 | *tert-butyl methyl ether*

5300 ppm

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

67-56-1 methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
-----	--

REL	Short-term value: 325 mg/m ³ , 250 ppm
	Long-term value: 260 mg/m ³ , 200 ppm
	Skin

TLV	Short-term value: 328 mg/m ³ , 250 ppm
	Long-term value: 262 mg/m ³ , 200 ppm
	Skin; BEI

71-43-2 benzene

PEL	Short-term value: 15* mg/m ³ , 5* ppm
	Long-term value: 3* mg/m ³ , 1* ppm
	*table Z-2 for exclusions in 29CFR1910.1028(d)

REL	Short-term value: 1 ppm
	Long-term value: 0.1 ppm
	See Pocket Guide App. A

TLV	Long-term value: 0.02 ppm
	Skin; BEI, AI

(Contd. on page 6)

— US —

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 5)

91-20-3 naphthalene*PEL* Long-term value: 50 mg/m³, 10 ppm*REL* Short-term value: 75 mg/m³, 15 ppmLong-term value: 50 mg/m³, 10 ppm*TLV* Long-term value: 52 mg/m³, 10 ppm

Skin; BEI, A3

100-41-4 ethylbenzene*PEL* Long-term value: 435 mg/m³, 100 ppm*REL* Short-term value: 545 mg/m³, 125 ppmLong-term value: 435 mg/m³, 100 ppm*TLV* Long-term value: 20 ppm

OTO, BEI, A3

108-88-3 toluene*PEL* Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppmLong-term value: 375 mg/m³, 100 ppm*TLV* Long-term value: 20 ppm

BEI, OTO, A4

Ingredients with biological limit values:**67-56-1 methanol***BEI* 15 mg/L

Medium: urine

Time: end of shift

Parameter: Methanol (background, nonspecific)

71-43-2 benzene*BEI* 25 µg/g creatinine

Medium: urine

Time: end of shift Parameter

Parameter: S-Phenylmercapturic acid (background

500 µg/g creatinine

Medium: urine

Time: end of shift

Parameter: t,t-Muconic acid (background)

91-20-3 naphthalene*BEI* -

Medium: -

Time: end of shift

Parameter: 1-Naphthol with hydrolysis + 2-Naphthol with hydrolysis (Nq,Ns)

100-41-4 ethylbenzene*BEI* 0.15 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 6)

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
------------	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

— US —
(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 7)

* 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Physical state	Liquid
· Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· Melting point/Melting range:	-98 °C (-144.4 °F)
· Boiling point/Boiling range:	64.7 °C (148.5 °F)
· Flammability:	Highly flammable.
· Explosion limits:	
· Lower:	5.5 Vol %
· Upper:	44 Vol %
· Flash point:	11 °C (51.8 °F)
· Auto igniting:	455 °C (851 °F)
· Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Dynamic:	Not determined.
· Solubility in / Miscibility with	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
· Vapor pressure:	
· Density at 20 °C (68 °F):	0.79095 g/cm ³ (6.60048 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Particle characteristics	Not applicable.

· Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Solvent content:	
· Organic solvents:	99.9 %
· VOC content:	99.90 %
	790.2 g/l / 6.59 lb/gal
· Solids content:	0.1 %
· Change in condition	
· Evaporation rate	Not determined.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 8)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	3.03 mg/l
------------	----------	-----------

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
------	------	-------------------

Dermal	LD50	15,800 mg/kg (rabbit)
--------	------	-----------------------

71-43-2 benzene

Oral	LD50	4,894 mg/kg (rat)
------	------	-------------------

Dermal	LD50	48 mg/kg (mouse)
--------	------	------------------

Inhalative	LC50/4 h	9,980 mg/l (mouse)
------------	----------	--------------------

91-20-3 naphthalene

Oral	LD50	490 mg/kg (rat)
------	------	-----------------

Dermal	LD50	5,000 mg/kg (rat)
--------	------	-------------------

100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
------	------	-------------------

Dermal	LD50	17,800 mg/kg (rabbit)
--------	------	-----------------------

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	12,124 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50/4 h	5,320 mg/l (mouse)
------------	----------	--------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Toxic
The product can cause inheritable damage.
- **Interactive effects** No interactive effects between components are known.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

71-43-2	benzene	1
91-20-3	naphthalene	2B
95-47-6	o-xylene	3
100-41-4	ethylbenzene	2B
106-42-3	p-xylene	3
108-38-3	m-xylene	3

(Contd. on page 10)

US —

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 9)

108-88-3	toluene	3
1634-04-4	tert-butyl methyl ether	3

· NTP (National Toxicology Program)		
71-43-2	benzene	K
91-20-3	naphthalene	R
· OSHA-Ca (Occupational Safety & Health Administration)		
71-43-2	benzene	

· **Alternative sources for toxicological information** No non-standard sources for toxicological information where used.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1992
· UN proper shipping name	
· DOT	Flammable liquids, toxic, n.o.s. (Methanol)
· IMDG	FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL)
· IATA	Flammable liquid, toxic, n.o.s. (METHANOL)

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 10)

· Transport hazard class(es) · DOT	
 	
· Class · Label	3 Flammable liquids 3, 6.1
· IMDG	
 	
· Class · Label	3 Flammable liquids 3/6.1
· IATA	
 	
· Class · Label	3 Flammable liquids 3 (6.1)
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	
	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Stowage Code	Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters.
· UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL), 3 (6.1), II

US —

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 11)

*15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-56-1 methanol

71-43-2 benzene

91-20-3 naphthalene

95-47-6 o-xylene

95-63-6 1,2,4-trimethylbenzene

100-41-4 ethylbenzene

106-42-3 p-xylene

108-38-3 m-xylene

108-88-3 toluene

1634-04-4 tert-butyl methyl ether

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

67-56-1 methanol

71-43-2 benzene

91-20-3 naphthalene

95-47-6 o-xylene

100-41-4 ethylbenzene

106-42-3 p-xylene

108-38-3 m-xylene

108-88-3 toluene

1634-04-4 tert-butyl methyl ether

· Proposition 65

· Chemicals known to cause cancer:

71-43-2 benzene

91-20-3 naphthalene

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

71-43-2 benzene

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

71-43-2 benzene

108-88-3 toluene

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 12)

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

71-43-2	benzene	A, K/L
91-20-3	naphthalene	C, CBD
95-47-6	o-xylene	I
95-63-6	1,2,4-trimethylbenzene	II
100-41-4	ethylbenzene	D
106-42-3	p-xylene	I
108-38-3	m-xylene	I
108-67-8	mesitylene	II
108-88-3	toluene	II

· **TLV (Threshold Limit Value)**

71-43-2	benzene	A1
91-20-3	naphthalene	A4
95-47-6	o-xylene	A4
100-41-4	ethylbenzene	A3
106-42-3	p-xylene	A4
108-38-3	m-xylene	A4
108-88-3	toluene	A4
1634-04-4	tert-butyl methyl ether	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

71-43-2	benzene
---------	---------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02 GHS06 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

methanol

benzene

toluene

ethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.

Toxic if inhaled.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to the central nervous system and the visual organs.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground / bond container and receiving equipment.

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 13)

Use explosion-proof [electrical/ventilating/lighting] equipment.
 Use non-sparking tools.
 Take action to prevent static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Specific treatment (see on this label).
 IF exposed or concerned: Get medical advice/attention.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** - Department Technical Manager

· **Date of previous version** 03/07/2024

· **Date of preparation** 06/30/2026

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable liquids 2: Flammable liquids – Category 2

Acute toxicity - inhalation 3: Acute toxicity – Category 3

Germ cell mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1A: Carcinogenicity – Category 1A

(Contd. on page 15)

Safety Data Sheet
acc. to OSHA HCS

Date of issue: 06/30/2026

Reviewed on 06/30/2026

Trade name: UST-360

(Contd. of page 14)

*Reproductive toxicity 2: Reproductive toxicity – Category 2**Specific target organ toxicity (single exposure) 1: Specific target organ toxicity (single exposure) – Category 1**· * Data compared to the previous version altered.*

US
